

SIGNET

NEXEN

DEESTONE

MUSTANG

NUTECH


TECHKING

DICK CEPEK

MICKEY THOMPSON

PARNELLI JONES

SOLIDEAL



HERCULES TIRES
RIDE ON OUR STRENGTH.

Tire sizes, data specifications and product availability changes frequently. While every effort has been made to verify the accuracy of this information, it should be considered as approximate and subject to change. Please check with your salesperson for the most recent updates.



16380 E. US 224 Suite 200
Findlay, OH 45840
Phone: 800-677-3573
www.herculestire.com



16380 E. US 224 Suite 200
Findlay, OH 45840
Phone: 800-677-3573
www.herculestire.com

96427 (09/07)

TABLE OF CONTENTS

SIGNET	page 2
NEXEN	pages 2 - 8
DEESTONE	pages 9 - 13
MUSTANG	page 14
NUTECH	page 15
TECHKING	page 16
DICK CEPEK	pages 17 - 19
MICKY THOMPSON	pages 20 - 30
PARNELLI JONES	page 31
SOLIDEAL	pages 32 - 39

Tire sizes, data specifications and product availability changes frequently. While every effort has been made to verify the accuracy of this information, it should be considered as approximate and subject to change. Please check with your salesperson for the most recent updates.

SIGNET



SIGNET DSR II

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
WHITE SIDEWALL - UTQG - 340 B B								
P185/75R14	02258	1290	35	5.0	7.2	24.8	10	16.0
P195/75R14	02260	1400	35	5.5	7.6	25.4	10	17.0
P205/75R14	02262	1532	35	5.5	8.0	26.0	10.5	19.0
P215/75R14	02264	1664	35	6.0	8.4	27.0	10.5	20.0
P205/75R15	02266	1598	35	5.5	8.0	27.0	10.5	20.0
P215/75R15	02268	1742	35	6.0	8.4	27.6	10.5	21.0
P225/75R15	02270	1874	35	6.0	8.7	28.1	10.5	23.0
P235/75R15	02272	2028	35	6.5	9.1	28.7	11	24.0

NEXEN



NEXEN N7000

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
55 SERIES - UTQG - 360 AA A								
205/55ZR16 94W	12177N	1477	50	6.5	8.4	24.9	10.0/32	22.6
215/55ZR16 97W	12168N	1609	50	7.0	8.9	25.3	10.0/32	24.3
235/55ZR17 99W	12197N	1709	44	7.5	9.6	27.2	10.0/32	29.1
215/55ZR17 94W	12170N	1433	44	7.0	8.9	26.3	10.0/32	24.3
50 SERIES - UTQG - 360 AA A								
215/50ZR17 91W	12179N	1356	44	7.0	8.9	25.5	10.0/32	23.5
45 SERIES - UTQG - 360 AA A								
205/45R16 87W	12155	1201	50	7.0	8.2	23.1	10.0/32	20.1
215/45R17 91W	12186	1356	50	7.0	8.5	24.6	10.0/32	22.6
225/45R17 91W	12187	1356	44	7.5	8.9	25.0	10.0/32	23.5
235/45R17 97W	12188	1609	50	8.0	9.4	25.3	10.0/32	26.4
245/45R17 95W	12189	1521	44	8.0	9.6	25.7	10.0/32	27.8
245/45R18 100W	12144	1764	50	8.0	9.6	26.7	10.0/32	29.6
255/45R18 103W	12191	1929	50	8.5	10.0	27.0	10.0/32	30.9
40 SERIES - UTQG - 360 AA A								
205/40R16 97W	12151	963	44	7.5	8.4	22.4	10.0/32	19.2
205/40R17 84W	12181	1102	50	7.5	8.4	23.5	10.0/32	20.5
215/40R17 87W	12182	1201	50	7.5	8.7	23.9	10.0/32	21.6
235/40R17 90W	12183	1323	44	8.5	9.6	24.3	10.0/32	24.0
245/40R17 95W	12190	1521	50	8.5	9.8	24.7	10.0/32	24.3
255/40R17 94W	12184	1477	44	9.0	10.2	25.0	10.0/32	26.3
275/40R17 98W	12185	1653	44	9.5	10.9	25.7	10.0/32	29.5
225/40R18 92W	12195	1389	50	8.0	9.1	25.1	10.0/32	23.2
235/40R18 93W	12160	1433	44	8.5	9.5	25.4	10.0/32	25.2
245/40R18 97W	12161	1609	50	8.5	9.8	25.7	10.0/32	26.0
35 SERIES - UTQG - 360 AA A								
215/35R18 84W	12154	1102	50	7.5	8.6	23.9	10.0/32	20.6
265/35R18 97W	12192	1609	50	9.5	10.7	25.3	10.0/32	26.8
275/35R18 95W	12194	1521	44	9.5	11.4	25.6	10.0/32	27.8
225/35R20 90W	12163	1609	50	8.5	9.5	25.5	10.0/32	24.5
245/35R20 95W	12164	1521	50	8.5	9.5	25.5	10.0/32	27.1
255/35R20 97W	12165	1609	50	9.0	10.2	27.0	10.0/32	28.3
30 SERIES - UTQG - 360 AA A								
225/30R20 90W	12193	1323	50	8.0	9.1	25.4	10.0/32	22.5

NEXEN N3000



SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
55 SERIES - UTQG - 340 AA A								
205/55R16 94W	12077	1477	50	6.5	8.4	24.9	9.8/32	24.4
215/55R16 97W	12078	1609	50	7.0	8.9	25.3	10.0/32	25.6
50 SERIES - UTQG - 340 AA A								
215/50R17 91W	12079	1356	44	7.0	8.9	25.5	10.0/32	24.4
225/50R17 94Y	12080	1477	44	7.0	9.2	25.9	10.1/32	27.3
45 SERIES - UTQG - 340 AA A								
195/45R15 78W	12053	937	44	6.5	7.8	21.9	9.8/32	17.6
205/45R16 87W	12055	1201	50	7.0	8.2	23.1	9.8/32	19.8
225/45R16 89W	12057	1279	44	7.5	8.9	23.9	9.8/32	22.3
245/45R16 94W	12059	1477	44	8.0	9.6	24.6	9.8/32	26.3
215/45R17 91W	12086	1356	50	7.0	8.5	24.6	9.8/32	22.2
225/45R17 91W	12087	1356	44	7.5	8.9	25.0	9.8/32	23.7
235/45R17 94W	12088	1477	44	8.0	9.4	25.3	9.8/32	26.1
245/45R17 95W	12089	1521	44	8.0	9.6	25.7	9.8/32	27.8
245/45R18 100Y	12044	1764	50	8.0	9.6	26.7	10.2/32	29.2
255/45R18 103Y	12054	1929	50	8.5	10.0	27.0	10.2/32	30.6
40 SERIES - UTQG - 340 AA A								
205/40R16 79W	12051	963	44	7.5	8.4	22.4	9.8/32	18.8
215/40R16 86W	12052	1168	50	7.5	8.7	22.7	9.8/32	20.0
205/40R17 84W	12081	1102	50	7.5	8.4	23.5	9.8/32	20.5
215/40R17 87W	12082	1201	50	7.5	8.7	23.9	9.8/32	21.3
235/40R17 90W	12083	1323	44	8.5	9.6	24.3	9.8/32	24.1
245/40R17 91W	12090	1365	44	8.5	9.8	24.7	10.2/32	24.2
255/40R17 94W	12084	1477	44	9.0	10.2	25.0	9.8/32	27.2
275/40R17 98W	12085	1653	44	9.5	10.9	25.7	10.2/32	29.0
225/40R18 92Y	12095	1389	50	8.0	9.1	25.1	10.2/32	23.0
235/40R18 93Y	12008	1433	44	8.5	9.5	25.4	10.2/32	25.4
245/40R18 97Y	12018	1609	50	8.5	9.8	25.7	10.2/32	25.8
35 SERIES - UTQG - 340 AA A								
215/35R18 84Y	12091	1102	50	7.5	8.6	23.9	10.2/32	20.3
255/35R18 94Y	12058	1477	50	9.0	10.2	25.0	10.2/32	25.6
265/35R18 97Y	12063	1609	50	9.5	10.7	25.3	10.2/32	27.1
275/35R18 95Y	12064	1521	44	9.5	10.9	25.6	10.2/32	27.1
235/35R19 91Y	12073	1356	50	8.5	9.5	25.5	10.2/32	23.3
245/35R19 93Y	12074	1433	50	8.5	9.8	25.8	10.2/32	24.2
225/35R20 90Y	12092	1323	50	8.0	9.1	26.2	10.2/32	25.1
245/35R20 95Y	12094	1521	50	8.5	9.8	26.8	10.2/32	26.7
255/35R20 97Y	12050	1609	50	9.0	10.2	27.0	10.2/32	29.9



NEXEN N2000

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
65 SERIES - UTQG - 440 A A								
215/65R16 98H	10878	1653	44	6.5	8.7	26.3	10.2/32	26.3
60 SERIES - UTQG - 440 A A								
205/60R16 92V	10874	1389	44	6.0	8.2	25.7	10.1/32	23.7
215/60R16 95H	10876	1521	44	6.5	8.6	26.0	10.2/32	24.9
235/60R16 100H	10882	1764	44	7.0	9.4	27.1	10.5/32	29.3
55 SERIES - UTQG - 340 AA A								
185/55R14 80H	10855	992	44	6.0	7.6	22.0	9.6/32	18.4
185/55R14 80V	10856	992	44	6.0	7.6	22.0	9.6/32	18.1
185/55R15 82V	10821	1047	44	6.0	7.6	23.0	9.6/32	18.8
195/55R15 85V	10865	1135	44	6.0	7.9	23.4	9.7/32	20.9
205/55R15 88V	10862	1235	44	6.5	8.4	23.9	9.8/32	23.5
205/55R16 91V	10824	1356	44	6.5	8.4	24.9	9.8/32	24.6
215/55R16 93V	10868	1433	44	7.0	8.9	25.3	10.0/32	26.1
225/55R16 95V	10906	1521	44	7.0	9.3	25.7	10.1/32	27.9
50 SERIES - UTQG - 340 AA A								
195/50R15 82H	10863	1047	44	6.0	7.9	22.7	9.7/32	19.0
195/50R15 82V	10864	1047	44	6.0	7.9	22.7	9.7/32	19.6
205/50R15 86V	10920	1168	44	6.5	8.5	23.1	9.8/32	22.7
225/50R15 91V	10867	1356	44	7.0	9.3	23.9	10.1/32	25.4
195/50R16 84V	10913	1102	44	6.0	8.0	23.7	9.7/32	22.3
205/50R16 87V	10720	1201	44	6.5	8.5	24.1	9.8/32	23.5
225/50R16 92V	10907	1389	44	7.0	9.3	24.9	10.1/32	25.9



NEXEN CP641

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
65 SERIES - UTQG - 400 A A								
175/65R14 82H	12469	1047	44	5.0	6.9	23.1	9/32	16.2
185/65R14 86H	12452	1168	44	5.5	7.4	23.5	10/32	18.0
195/65R14 89H	12491	1279	44	6.0	7.8	24.1	10/32	19.4
185/65R15 88H	12436	1235	44	5.5	7.3	24.6	10/32	18.6
195/65R15 91H	12437	1356	44	6.0	7.7	25.1	10/32	19.7
205/65R14 91H	12392N	1356	44	6.0	8.2	24.5	10/32	20.9
205/65R15 94H	12493	1477	44	6.0	8.0	25.6	10/32	21.8
215/65R15 96H	12477	1565	44	6.5	8.6	26.2	10/32	24.3
205/65R16 95H	12466	1521	44	6.0	8.2	26.5	10/32	-
215/65R16 98H	12488	1653	44	6.5	8.7	26.3	10/32	25.6
60 SERIES - UTQG - 400 A A								
185/60R13 80H	12440	992	44	5.5	7.1	21.8	10/32	16.0
185/60R14 82H	12472	1047	44	5.5	7.2	22.7	10/32	17.0
195/60R14 86H	12427	1168	44	6.0	7.9	23.2	10/32	19.0
205/60R14 88H	12485	1235	44	6.0	8.1	23.7	10/32	20.1
215/60R14 91H	12484	1356	44	6.5	8.6	24.1	10/32	21.3

NEXEN CP641 *continued*

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
60 SERIES - UTQG - 400 A A								
185/60R15 84H	12473	1102	44	5.5	7.4	23.7	10/32	18.1
195/60R15 88H	12420	1235	44	6.0	7.8	24.2	10/32	19.9
205/60R15 91H	12441	1356	44	6.0	8.1	24.7	10/32	21.0
215/60R15 94H	12475	1477	44	6.5	8.6	25.1	10/32	22.3
225/60R15 96H	12480	1565	44	6.5	8.9	25.6	10/32	25.0
205/60R16 92V	10874	1389	44	6.0	8.2	25.7	10/32	-
215/60R16 95H	12476	1521	44	6.5	8.6	26.0	10/32	23.6
225/60R16 98H	12481	1653	44	6.5	8.9	26.5	10/32	26.3
235/60R16 100H	12482	1764	44	7.0	9.4	27.1	10/32	28.0
55 SERIES - UTQG - 400 A A								
195/55R15 85V	12465	1135	44	6	7.9	23.4	10/32	-
205/55R16 91V	12404	1356	44	6.5	8.4	24.9	10/32	23.9
215/55R16 93V	12468	1433	44	7.0	8.9	25.3	10/32	25.9
225/55R16 95V	12406	1521	44	7.0	9.3	25.7	10/32	28.4
50 SERIES - UTQG - 400 A A								
195/50R15 82V	12463	1047	44	6.0	7.9	22.7	10/32	19.1
205/50R15 86V	12455	1168	44	6.5	8.5	23.1	10/32	-
205/50R16 97V	12456	1201	44	6.5	8.5	24.1	10/32	23.7
225/50R16 92V	12407	1389	44	7.0	9.3	24.9	10/32	24.7
215/50R17 91V	12479	1323	44	7.0	8.9	25.5	10/32	24.9
225/50R17 94V	12457	1477	44	7.0	9.2	25.9	10/32	27.9



NEXEN S702

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
80 SERIES - UTQG - 320 A B								
155/80R13 79T	11733	959	44	4.5	6.2	22.8	10/32	14.4
165/80R13 83T	11734	1080	36	4.5	6.5	23.5	10/32	15.1
165/80R15 87T	11766	1201	36	4.5	6.5	25.5	10/32	17.6
70 SERIES - UTQG - 400 A B								
165/70R13 79T	10788	919	36	5.0	6.7	22.2	8/32	14.0
175/70R13 82T	10701	1036	44	5.0	7.0	22.7	9/32	15.5
185/70R13 86T	10707	1140	36	5.5	7.3	23.2	9/32	17.0
175/70R14 84T	10843	1102	36	5.0	7.0	23.7	9/32	17.2
185/70R14 88T	10702	1210	36	5.5	7.3	24.2	9/32	18.2
195/70R14 91T	10708	1340	36	6.0	8.0	24.8	9/32	18.7
205/70R14 95T	10759	1488	36	6.0	8.2	25.3	9/32	22.3
205/70R15 95T	10760	1488	36	6.0	8.0	26.3	10/32	23.6
215/70R15 98T	10586	1653	44	6.5	8.7	26.8	10/32	25.2
225/70R16 102T	10591	1874	44	6.5	8.9	28.3	10/32	-
WHITEWALL								
P205/70R15 95T	10758	1499	36	6.0	8.0	26.3	10/32	23.8
P215/70R15 97T	10587	1620	44	6.5	8.7	26.8	10/32	25.7



NEXEN



NEXEN SV820

SIZE	CODE #	MAX LOAD SINGLE	MAX LOAD DUAL	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
185R14/8	10209	1874	1765	65	5.5	7.4	25.7	11/32	24.3
195R14/8	10558	2094	1985	65	5.5	7.5	26.4	12/32	26.2



NEXEN ROADIAN HP

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
65 SERIES - UTQG - 460 A A								
235/65R17 108V	15465	2205	50	7.0	9.4	29.1	11/32	31.8
60 SERIES - UTQG - 460 A A								
265/60R17 108V	15451	2205	44	8.0	10.7	29.5	11/32	37.2
275/60R17 110V	15453	2337	44	8.0	11.0	30.0	11/32	38.4
265/60R18 110H	15608	2337	44	8.0	10.7	30.5	11/32	38.6
285/60R18 116V	15455	2756	44	8.5	11.5	31.5	11/32	41.5
55 SERIES - UTQG - 460 A A								
255/55R18 109V	15558	2271	50	8.0	10.4	29.0	11/32	35.7
45 SERIES - UTQG - 460 A A								
275/45R20 110V	15454	2337	50	9.0	10.7	29.8	11/32	36.1
295/45R20 114V	15459	2601	50	10.0	11.7	30.5	11/32	39.0
285/45R22 114V	15466	2601	50	9.5	11.2	32.1	11/32	38.6
305/45R22 118V	15452	2910	50	10.0	11.9	32.8	11/32	47.7
40 SERIES - UTQG - 460 A A								
295/40R20 106V	15463	2094	44	10.5	11.9	29.3	11/32	37.2
305/40R22 114V	15460	2601	50	11.0	12.3	31.6	11/32	44.7
35 SERIES - UTQG - 460 A A								
265/35R22 102V	15456	1874	50	9.5	10.7	29.3	11/32	33.5
305/35R24 112V	15354	2469	50	11.0	12.3	32.4	11/32	47.1
30 SERIES - UTQG - 460 A A								
255/30R22 92V	15464	1389	50	9.0	10.2	26.1	11/32	29.0
295/30R22 103V	15457	1929	50	10.5	11.9	29.0	11/32	35.5

NEXEN ROADIAN HT SUV

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
OUTLINED WHITE LETTER								
75 SERIES - UTQG - 520 A B								
P215/75R15 100S	14546	1742	44	6.0	8.5	27.7	12/32	27.5
P235/75R15 105S	14747	2028	44	6.5	9.3	28.9	12/32	31.3
P225/75R16 104S	14553	1984	44	6.0	9.2	29.3	12/32	30.0
P245/75R16 109S	14443	2271	44	7.0	9.8	30.5	12/32	34.8
P265/75R16 114S	14529	2601	44	7.5	10.5	31.7	12/32	43.0
70 SERIES - UTQG - 520 A B								
P225/70R15 100S	14851	1753	44	6.5	9.0	27.4	12/32	28.3
P235/70R15 102S	14852	1896	44	7.0	9.4	28.0	12/32	29.8
P255/70R15 108S	14428	2183	44	7.5	10.2	29.1	12/32	32.6
P265/70R15 110S	14429	2337	44	8.0	10.7	29.6	12/32	36.4
P235/70R16 104S	14854	1984	44	7.0	9.4	29.0	12/32	30.6
P245/70R16 107S	14855	2149	44	7.0	9.8	29.5	12/32	32.8
P255/70R16 109S	14856	2271	44	7.5	10.2	30.1	12/32	36.8
P265/70R16 112S	14857	2469	44	8.0	10.7	30.6	12/32	37.2
P275/70R16 114S	14860	2601	44	8.0	11.0	31.2	12/32	41.4
P245/70R17 110S	14864	2337	44	7.0	9.8	30.6	12/32	34.2
P265/70R17 113S	14862	2469	44	8.0	11.1	30.6	12/32	39.8
65 SERIES - UTQG - 520 A B								
P235/65R17 104S	14859	1984	44	7.0	9.4	29.1	12/32	30.6
P245/65R17 105S	14952	2149	44	7.0	9.8	29.5	12/32	33.3



NEXEN ROADIAN HT LT

SIZE	CODE #	MAX LOAD SINGLE	MAX LOAD DUAL	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
OUTLINED WHITE LETTER									
LT215/75R15/6	13146	1764	1610	50	6.0	8.5	27.7	14/32	30.8
LT235/75R15/6	13247	1984	1820	50	6.5	9.3	28.9	14/32	34.6
30X9.50R15/6	13417	1984		50	7.5	9.4	29.5	15/32	36.7
31X10.50R15/6	13421	2271		50	8.5	10.6	30.5	15/32	41.3
LT245/75R16/10	13443	3042	2778	80	7.0	9.8	30.5	15/32	41.9
LT265/75R16/10	13629	3686	3415	80	7.5	10.5	31.7	15/32	47.7
BLACKWALL									
LT225/75R16/10	13653	2679	2470	80	6.0	8.8	29.3	15/32	37.9
LT215/85R16/10	13506	2679	2470	80	6.0	8.5	30.4	15/32	39.4
LT235/85R16/10	13415	3042	2778	80	6.5	9.3	31.7	15/32	46.9



NEXEN



NEXEN ROADIAN AT

SIZE	CODE #	MAX LOAD	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
BLACKWALL UTQG 500 A B								
P255/65R16 106T	10850	2094	44	7.5	10.4	28.9	11/32	33.8
P235/70R16 104T	10854	1984	44	7.0	9.7	28.8	11/32	29.7



NEXEN ROADIAN AT II

SIZE	CODE #	MAX LOAD SINGLE	MAX LOAD DUAL	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
OUTLINED WHITE LETTER UTQG 560 A B									
P235/65R17	14859	2205		50	7.0	9.4	29.1	11/32	
P245/65R17	14952	2039		44	7.0	9.8	29.5	12/32	
P245/70R17	14864	2205		44	7.0	9.8	30.6	12/33	
LT235/75R15/6	13747	1984	1820	50	6.5	9.2	28.9	15/32	34.7
LT225/75R16/10	13753	2679	2470	80	6.0	8.8	29.3	15/32	39.1
LT245/75R16/10	13743	3042	2778	80	7.0	9.8	30.4	15/32	43.1
LT265/75R16/10	13729	3415	3085	80	7.5	10.5	31.7	15/32	47.4
P265/70R17 113S	13762	2535		35	8.0	10.7	31.7	15/32	37.4
LT265/70R17/6	13712	2469	2270	50	8.0	11.0	32.2	15/32	41.6
LT215/85R16/10	13706	2679	2469	80	6.0	8.3	30.5	15/32	39.1
LT235/85R16/10	13715	3042	2778	80	6.5	9.1	31.8	15/32	44.7
30X9.50R15/6	13717	1985		50	7.5	9.7	29.5	15/32	37.4
31X10.50R15/6	13721	2270		50	8.5	10.7	30.5	15/32	41.5



NEXEN ROADIAN MT

SIZE	CODE #	MAX LOAD SINGLE	MAX LOAD DUAL	MAX PSI	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
OUTLINED WHITE LETTER									
27x8.50R14 95Q		1520		50	7	8.6	26.5	-	-
LT235/75R15/6	10667	1984	1820	50	6.0	9.2	28.9	17/32	36.8
LT265/75R16/8	10650	2998	2755	65	7.5	10.5	31.7	17/32	47.2
LT235/85R16/10	10658	3042	2778	80	6.5	9.3	31.7	17/32	46.9
31X10.50R15/6	10674	2271		50	8.5	10.6	30.5	18/32	42.2

DEESTONE

DEESTONE BOAT TRAILER TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
4.80-8/4	DS7250	D901	TLS	16.7	4.6	5.38	7.00
4.80-8/6	DS7251	D901	TLS	16.7	4.6	5.60	7.00
4.80/4.00-8/6	DS7285	D95 "E"	TT	16.7	4.7	5.15	6.00
4.80-12/4	DS7265	D901	TLS	21.3	5.2	8.51	7.00
4.80-12/6	DS7266	D901	TLS	21.3	5.2	9.41	7.00
5.00-10/8	DS7260	D901	TLS	20.3	5.5	10.64	11.00
5.30-12/6	DS7271	D901	TLS	22.1	5.3	11.20	7.00
5.30-12/8	DS7272	D901	TLS	22.1	5.3	11.87	7.00
5.70-8/6	DS7256	D901	TLS	18.6	5.6	9.18	8.00
5.70-8/8	DS7257	D901	TLS	18.6	5.6	9.52	8.00
A78-13/6	DS7273	D622	TLS	23.3	6.3	15.20	10.00
B78-13/6	DS7275	D901	TLS	24.4	6.8	16.00	10.00
C78-13/6	DS7283	D622	TLS	24.8	7.3	17.60	6.00
E78-14/6	DS7294	D622	TLS	26.3	7.9	21.00	11.00
F78-14/6	DS7277	D901	TLS	26.7	7.8	22.00	11.00
G78-14/6	DS7279	D901	TLS	27.2	8.2	24.00	11.00
F78-15/6	DS7278	D901	TLS	27.2	7.5	22.00	11.00
H78-15/8	DS7281	D901	TLS	28.5	8.5	27.00	12.00



DEESTONE LOW PROFILE HIGH SPEED TRAILER TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
16.5X6.50-8/4	DS7100	D268	TLS	16.3	6.80	8.50	5.00
16.5X6.50-8/6	DS7101	D268	TLS	16.3	6.80	8.74	5.00
18.5X8.50-8/4	DS7105	D268	TLS	18.1	8.40	11.87	7.00
18.5X8.50-8/6	DS7106	D268	TLS	18.1	8.40	12.54	7.00
20.5X8.00-10/6	DS7111	D268	TLS	20.6	8.10	15.01	8.00
20.5X8.00-10/8	DS7112	D268	TLS	20.6	8.10	15.68	8.00
20.5X8.00-10/10	DS7113	D268	TLS	20.6	8.10	15.90	8.00
20.5X8.00-10/12	DS7114	D268	TLS	20.6	8.10	16.10	8.00

DEESTONE LPT / TRAILER / LT TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
7-14.5/12	DS6316	D292	TLS	26.7	7.6	24.00	8.00
8-14.5/12	DS6318	D292	TLS	28	8.0	27.00	8.00
9-14.5/12	DS6315	D902	TLS	27.8	8.9	40.00	8.00
7.50-15/12	DS6320	D902	TT	31	8.3	43.00	15.00
8.25-15/14	DS6323	D902	TT	33.1	9.4	54.00	15.00
9.00-15/12	DS6330	D902	TT	34.7	10.3	58.00	15.00
10.00-15/14	DS6335	D902	TT	36.3	11.2	72.00	18.00
8.75-16.5/10	DS1290	D902	TLS	30.1	9.0	38.00	14.00
9.50-16.5/10	DS1295	D902	TLS	30.7	9.7	44.00	14.00
12-16.5/12	DS7906	D905	TLS	33.4	12.9	64.00	17.00

DEESTONE



DEESTONE WHEEL BARROW TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
3.50-8/2	DS7150	D601	TLS	14.7	3.4	2.13	3.10
4.00/4.80-8/4	DS7160	D601	TLS	16	4	2.64	3.10
3.25/3.00-8/2	DS7165	D602	TLS	14.4	3.5	2.24	3.10
3.50-8/2	DS7170	D602	TLS	14.7	3.4	2.13	3.10
4.00/4.80-8/2	DS7175	D602	TLS	16.0	4.0	2.42	4.00
4.00/4.80-8/4	DS7178	D602	TLS	16.0	4.0	2.64	4.00

DEESTONE LAWN AND GARDEN TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
4.10/3.50-4/4	DS7201	D256	TLS	10.7	3.80	2.46	6.00
4.00/4.80-8/4	DS3333	D256	TLS	16.2	4.80	5.26	5.26
4.00-4/4	DS7001	D265	TLS	11.5	4.2	2.58	5.00
4.10/3.50-4/4	DS7011	D265	TLS	10.8	3.90	2.58	5.00
4.80/4.00-8/4	DS7013	D265	TLS	16.3	4.80	5.38	5.00
11X4.00-4/4	DS7014	D265	TLS	10.8	4.00	2.80	6.00
11X4.00-5/4	DS7016	D265	TLS	11	3.90	2.69	5.00
13X5.00-6/4	DS7021	D265	TLS	13	4.30	3.58	7.00
13X6.50-6/4	DS7029	D265	TLS	13	6.30	4.70	6.00
15X6.00-6/4	DS7026	D265	TLS	14.9	6.20	5.82	7.00
16X6.50-8/4	DS7031	D265	TLS	15.9	6.60	7.62	7.00
16X7.50-8/4	DS7036	D265	TLS	16.2	7.00	7.39	5.00
18X6.50-8/4	DS7033	D265	TLS	17.6	6.90	8.96	7.00
18X8.50-8/4	DS7037	D265	TLS	17.7	8.00	10.08	7.00
18X9.50-8/4	DS7040	D265	TLS	17.7	8.70	9.63	7.00
20X8.00-8/4	DS7042	D265	TLS	19.4	8.60	9.97	6.00
20X10.00-8/4	DS7043	D265	TLS	19.5	9.10	12.32	7.00
20X10.00-10/4	DS7045	D265	TLS	20.5	9.60	12.77	7.00
23X8.50-12/4	DS7049	D265	TLS	22.8	8.10	14.11	7.00
23X9.50-12/4	DS7081	D265	TLS	23	8.90	14.78	7.00
23X10.50-12/4	DS7083	D265	TLS	23.2	9.90	17.70	9.00
26X12.00-12/4	DS7084	D265	TLS	25.28	12.40	24.25	9.00
26X12.00-12/6	DS7085	D265	TLS	25.28	12.40	24.25	9.00
11X4.00-5/4	DS7095	D266	TLS	10.6	4.00	2.69	4.00
15X6.00-6/4	DS7097	D266	TLS	14.5	5.30	5.15	5.00
16X6.50-8/4	DS7099	D266	TLS	15.6	6.40	7.84	5.00
18X7.50-8/4	DS7051	D266	TLS	17.8	7.30	9.30	7.00
18X8.50-8/4	DS7056	D266	TLS	18.1	8.30	9.86	8.00
18X9.50-8/4	DS7061	D266	TLS	17.6	8.60	11.76	8.00
20X10.00-8/4	DS7066	D266	TLS	19.7	9.70	12.32	7.00
20x10.00-10/6	DS7067	D266	TLS	19.7	9.20	14.11	8.00

DEESTONE

DEESTONE LAWN AND GARDEN TIRES *continued*

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
20X10.00-10/4	DS7070	D266	TLS	19.6	9.30	14.11	8.00
23X10.50-12/4	DS7069	D266	TLS	23	9.80	15.90	8.00
22X11.00-8/4	DS7091	D267	TLS	21.7	10.50	13.44	8.00
18X8.50-8/4	DS7093	D270	TLS	17.9	8.00	10.53	6.00
4.10/3.50-4/4	DS7200	D289	TLS	10.7	3.80	2.46	5.00
4.00/4.80-8/4	DS7204	D289	TLS	16.2	4.80	2.00	-
2.50-4/4	DS7186	D603	TLS	8.5	2.40	1.12	4.00
3.00-4/2	DS7191	D603	TLS	10.4	3.50	1.30	4.00
4.10/3.50-5/4	DS7212	D604	TLS	11.7	3.90	2.24	7.00
4.10/3.50-6/4	DS7203	D605	TLS	12.8	4.2	2.60	7.00
11X4.00-4/4	DS7209	D837	TLS	11.3	4.10	2.69	2.00
11X4.00-5/4	DS7210	D837	TLS	11.2	4.00	2.58	2.00
13X5.00-6/4	DS7211	D837	TLS	12.9	4.60	3.58	4.00
13X6.50-6/4	DS7214	D837	TLS	13	6.30	4.70	4.00
15X6.00-6/4	DS7216	D837	TLS	14.4	5.90	5.15	5.00
16X6.50-8/4	DS7221	D837	TLS	16	6.90	7.50	5.00
18X8.50-8/4	DS7226	D837	TLS	17.8	8.20	9.86	5.00

DEESTONE GO-KART TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
10X4.50-5/4	DS7290	D191		9.96	5.1	2.58	5.00
11X6.00-5/4		D191		-	-	-	-
11X7.10-5/4	DS7295	D190		10.67	8.27	4.70	5.00

DEESTONE AGRICULTURAL TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
3.50-6/4	DS5100	D401	TT	13.5	3.9	3.10	3.10
4.00-6/4		D401	TT	14.5	4.3	6.00	8.00
3.50-8/4	DS5102	D401	TT	15.4	3.4	4.48	8.00
4.00-8/4	DS5106	D401	TT	16.4	4.2	6.40	10.00
4.00-10/4	DS5110	D401	TT	18.6	4.2	9.20	14.00
4.00-12/4	DS5115	D401	TT	21.1	4.7	10.00	14.00
5.60-13/6	DS5118	D401	TT	25	6.3	7.00	28.00
5.00-15/4	DS5120	D401	TT	26.3	6.4	8.00	28.00
5.00-15/6	DS5121	D401	TT	26.3	6.4	9.00	28.00
5.50-16/4	DS5122	D401	TT	28.8	6.3	17.60	20.00
5.50-16/6	DS5123	D401	TT	28.8	6.3	18.10	20.00
6.00-16/6	DS5125	D401	TT	28.5	6.9	22.50	28.00
6.50-16/6	DS5126	D401	TT	29.9	6.89	26.00	-
7.50-16/8	DS5128	D401	TT	32.4	8.6	33.80	28.00

DEESTONE

DEESTONE AGRICULTURAL TIRES *continued*

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
9.00-16/10	DS5130	D401	TT	34.3	8.9	49.00	28.00
10.00-16/8	DS5135	D401	TT	36.1	9.9	54.00	28.00
10.00-16/10	DS5136	D401	TT	36.1	9.9	58.00	28.00
11.00-16/8	DS5140	D401	TT	37.9	11.3	60.00	28.00
11.00-16/10	DS5141	D401	TT	37.9	11.3	66.00	28.00
7.50-18/8	DS5150	D401	TT	34.1	8.6	40.70	28.00
4.00-19/4	DS5153	D401	TT	28.7	4.3	24.00	-
6.00-19/8	DS5155	D401	TT	32.4	7	29.00	28.00
3.50-5/4		D405	TT	12	3.8	2.90	-
3.50-6/4	DS5200	D405	TT	12.5	3.9	2.80	-
3.50-7/4		D405	TT	13.8	3.9	3.00	-
4.00-8/4	DS5211	D405	TT	16.7	4.3	6.40	26.00
4.00-8/4	DS5212	D405	TLS	16.7	4.3	6.40	26.00
4.00-9/4		D405	TT	-	-	-	26.00
4.00-10/4	DS5220	D405	TT	18.6	4.2	9.20	23.00
6.00-14/6	DS5260	D405	TT	26.6	6.6	23.20	-
7.50-16/8	DS5280	D405	TT	31.7	8.2	36.30	-
23X8.50-12/4	DS5240	D405	TLS	22.9	8.2	16.00	15.00
23X8.50-12/6	DS5241	D405	TLS	22.9	8.2	16.00	15.00
23X8.50-12/8		D405	TLS	22.9	8.2	17.00	15.00
23X8.50-12/10	DS5243	D405	TLS	22.9	8.2	18.00	15.00
23X10.50-12/4	DS5245	D405	TLS	23.3	9.6	22.00	16.00
23X10.50-12/6	DS5246	D405	TLS	23.3	9.6	22.00	16.00
23X10.50-12/8	DS5247	D405	TLS	23.3	9.6	22.00	16.00
23X10.50-12/10	DS5250	D405	TLS	23.3	9.6	23.00	16.00
26X12.00-12/6	DS5252	D405	TLS	25.4	11.6	30.00	23.00
13X5.00-6/4	DS5290	D407	TLS	12.8	4.9	4.00	10.00
16X6.50-8/4	DS5291	D407	TLS	15.6	6.5	8.00	13.00
26X12.00-12/8	DS5324	D408	TLS	25.4	11.8	31.00	23.00
26X12.00-12/10	DS5336	D408	TLS	25.4	11.8	32.00	23.00

DEESTONE RANCHER TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
11.5/80-15.3/14	DS6100	D315	TLS	-	-	-	-
12.5/80-15.3/14	DS6101	D315	TLS	-	-	-	-
10.0/75-15.3/8	DS5270	D403	TT	-	-	-	28.00
10.0/75-15.3/8	DS5271	D403	TLS	-	-	-	28.00
11.5/80-15.3/8	DS5275	D403	TT	-	-	-	28.00
11.5/80-15.3/8	DS5277	D403	TLS	-	-	-	28.00
405/70-20/14	DS5276	D403	TLS	-	-	-	38.00

DEESTONE TRENCHER TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
31X15.5-15/10	DS8001	D316	TLS	-	-	-	-

DEESTONE ATV TIRES

SIZE	CODE #	TREAD DESIGN	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
22X11.00-8/4	DS7301	D928	TLS	22.1	10.5	21.28	17.00
22X11.00-8/6		D928	TLS	22.1	10.5	21.28	17.00
16X8.00-7/4	DS7311	D929	TLS	16.5	7.2	6.72	12.00
20X7.00-8/4	DS7316	D929	TLS	19.8	6.5	8.96	12.00
22X11.00-8/4	DS7321	D929	TLS	22.8	9	12.99	15.00
25X12.00-9/2		D929	TLS	23.7	10.6	16.35	17.00
25X12.00-9/4	DS7325	D929	TLS	23.8	10.6	16.35	17.00
16X6.50-8/4	DS7330	D930	TLS	15.9	6.5	7.62	14.00
22X11.00-8/6	DS7341	D930	TLS	22	9.5	16.13	17.00
22X11.00-9/6	DS7345	D930	TLS	22.4	9.6	16.80	17.00
25X12.00-9/6	DS7350	D930	TLS	24.3	10.2	18.14	17.00
22X11.00-10/6	DS7360	D930	TLS	22.2	10.8	18.37	17.00
24X11.00-10/6	DS7365	D930	TLS	23.8	9.3	17.02	17.00
25X12.00-10/4	DS7371	D930	TLS	23.8	10.8	16.13	17.00
23X8.00-11/4	DS7375	D930	TLS	23.4	7.4	15.01	17.00
24X9.00-11/4	DS7380	D930	TLS	23.8	8.2	15.68	17.00
24X10.00-11/4	DS7383	D930	TLS	24.8	8.3	17.02	17.00
25X8.00-12/4	DS7389	D930	TLS	24.7	8	16.80	20.00
25X10.00-12/4	DS7391	D930	TLS	24.8	9.4	19.04	20.00
22X11.00-9/6	DS7920	D932	TLS	22.5	10.8	20.00	-
25X12.00-9/6	DS7925	D932	TLS	-	-	-	-
22X11.00-10/6	DS7921	D932	TLS	22.2	10.7	21.00	-
24X11.00-10/6	DS7924	D932	TLS	24.1	11.1	24.30	-
25X12.00-10/6	DS7926	D932	TLS	-	-	-	-
25X8.00-12/4	DS7389	D932	TLS	25	8.1	20.30	28.00
25X8.00-12/6	DS7932	D932	TLS	25	8.1	20.30	28.00
25X10.00-12/4		D932	TLS	25.2	10.1	26.40	28.00
25X10.00-12/6	DS7931	D932	TLS	25.2	10.1	26.40	28.00
26X10.00-12/6	DS7933	D932	TLS	26.1	8.8	27.30	-
26X12.00-12/6	DS7934	D932	TLS	25.9	11.8	32.60	-
27X10.00-12/6	DS7935	D932	TLS	26.7	9.8	29.80	-
27X12.00-12/6	DS7936	D932	TLS	26.8	11.9	32.80	-
28X10.00-12/6	DS7401	D932	TLS	27.9	10	31.30	-
28X12.00-12/6	DS7902	D932	TLS	27.9	12.2	33.10	-
23X8.00-11/6	DS7436	D933	TLS	-	-	-	-
24X9.00-11/6	DS7438	D933	TLS	-	-	-	-
25X8.00-12/6	DS7441	D933	TLS	-	-	-	-
25X10.00-12/6	DS7443	D933	TLS	-	-	-	-



MUSTANG

MUSTANG G2/L2

SIZE	MFR #	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
13.00-24/12	-	TL	50.1	-	140	29
13.00-24/16	MUS8003	TL	50.1	-	150	29
14.00-24/12	MUS8005	TL	52.8	-	167	31
14.00-24/16	MUS8007	TL	52.8	-	180	31
15.5-25/12	MUS8012	TL	50.6	-	177	30
17.5-25/16	MUS8017	TL	53.8	-	250	34
20.5-25/16	MUS8020	TL	59.1	-	331	35

MUSTANG E3/L3

SIZE	MFR #	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
29.5-29/34	MUS8170	TL	77.8	-	1302	54
16.00-25/32	MUS8321	TL	58.7	-	442	38
18.00-25/32	MUS8331	TL	63.6	-	540	40

MUSTANG E4

SIZE	MFR #	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
21.00-35/36	MUS8452	TL	80.4	-	1254	68
24.00-35/42	MUS8460	TL	85.0	-	1517	68
24.00-35/48	MUS8462	TL	85.0	-	1612	68
27.00-49/48	-	TL	106.0	-	2728	80
30.00-51/50	MUS8750	TL	115.6	-	-	88

MUSTANG L5

SIZE	MFR #	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
23.5-25/28	MUS9028	TL	65.7	-	983	99
26.5-25/36	MUS9036	TL	70.8	-	1435	110
29.5-25/32	MUS9042	TL	75.7	-	1595	128
29.5-29/36	MUS9056	TL	80.8	-	1827	128
45/65-45/38	MUS9000	TL	107.6	-	-	148

MUSTANG L5S

SIZE	MFR #	TUBELESS / TUBETYPE	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
26.5-25/28	MUS9100	TL	70.9	-	1654	110
29.5-25/32	MUS9112	TL	75.7	-	1846	123
29.5-29/36	MUS9124	TL	80.9	-	2010	123

NUTECH

NUTECH N100 HIGHWAY

TIRE - TUBE - FLAP						
TUBETYPE	CODE #	MFR #	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
8.25-20/14	38925	DNU3012	38.3	9.3	59.5	15
9.00-20/14	38926	DNU3015	40.1	10.2	68.5	15
10.00-20/14	38927	DNU3021	41.5	10.9	77.5	16
10.00-20/16	38928	DNU3022	41.5	10.9	84.0	16
11.00-20/16	38930	DNU3027	42.7	11.5	88.0	19
12.00-20/18	38931	DNU3031	44.3	12.4	111.8	23



NUTECH N500 TRACTION

TIRE - TUBE - FLAP						
TUBETYPE	CODE #	MFR #	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
8.25-20/14	38932	DNU3212	38.3	9.3	59.5	19
9.00-20/14	38933	DNU3215	40.1	10.2	68.5	19
10.00-20/16	38934	DNU3222	41.5	10.9	77.5	19
11.00-20/16	38935	DNU3227	42.7	11.5	88.0	19
12.00-20/18	38936	DNU3231	44.3	12.4	111.8	23

NUTECH II TRAILER

TIRE - TUBE - FLAP						
TUBETYPE	CODE #	MFR #	OVERALL DIAMETER	SECTION WIDTH	WEIGHT	TREAD DEPTH
10.00-20/14	37438	-	41.7	-	89.5	14
TUBELESS		-				
11-22.5/14	44835	-	41.6	-	78.0	14



TECHKING

TECHKING OFF THE ROAD TIRES



ET5A - E3/L3



ET6A - E3/L3



ETDT - E4



ETMINEA - L5

SIZE	CODE #	PATTERN	STAR RATING	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	LOAD (LBS) / INFLATION (PSI)	
							SPEED INDEX B	SPEED INDEX A2
17.5R25	-	ET5A L3/E3	2	35	17.5	53.1	12000 / 76	18700 / 94
20.5R25	44581	ET5A L3/E3	2	39	20.5	58.7	16100 / 76	25400 / 94
	-	ETMINEA L5	2	93	20.5	60.9	16100 / 76	25400 / 94
23.5R25	44582	ET5A L3/E3	2	43	23.5	63.7	20400 / 76	32000 / 94
	-	ETMINEA L5	2	105	26.5	65.9	20400 / 76	32000 / 94
26.5R25	44950	ET5A L3/E3	2	47	26.5	68.9	25400 / 76	40800 / 94
	-	ETSM L5S	2	110	26.5	70.8	25400 / 76	40800 / 94
29.5R25	44951	ET6A L3/E3	2	55	29.5	73.8	30900 / 76	49400 / 94
	-	E4	2	77	29.5	75.6	30900 / 76	49400 / 94
	-	ETSM L5S	2	123	29.5	75.6	30900 / 76	49400 / 94
29.5R29	-	ET6A L3/E3	2	52	29.5	77.8	33100 / 76	52000 / 94
	-	ETSM L5S	2	137	29.5	79.7	33100 / 76	52000 / 94
16.00R25	46024	ET5A L3/E3	2	35	17	58.8	16100 / 102	26800 / 120
18.00R25	46025	ETRT E4	2	59	19.6	65.9	20400 / 102	35300 / 120
18.00R33	-	ETDT E4	2	68	19.6	73.9	24000 / 102	40800 / 120

DICK CEPEK

RADIAL F-CII

OFF-ROAD RADIAL

SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
31X10.50R15/6	11053		41	2,270	50	7.0 - 9.0	8.5	10.7	8.2	31.0	18.0
33X12.50R15/6	13253		52	2,205	35	8.5 - 11.0	10.0	12.4	9.8	33.0	20.0
33X15.50R15/6	13553		83	2,405	35	11.0 - 13.0	12.0	15.7	12.1	32.9	22.0
35X12.50R15/6	15253		64	2,535	35	8.5 - 11.0	10.0	12.9	10.2	35.0	20.0
36X15.50R15/6	16553		92	3,000	35	11.0 - 13.0	12.0	15.6	12.2	35.8	22.0
37X13.50R15/6	17353		88	3,000	35	8.5 - 11.0	11.0	13.6	10.8	37.0	22.0
38X15.50R15/6	18553		97	3,415	35	11.0 - 13.0	12.0	15.7	12.2	37.8	22.0
LT265/75R16/10	12065	32X10.50R16LT	51	3,415	80	7.0 - 8.0	7.5	10.6	8.1	32.0	18.0
LT285/75R16/8	13164	33X11.50R16LT	54	3,305	65	7.0-9.0	8.0	11.3	9.2	33.0	20.0
LT305/70R16/8	13264	33X12.50R16LT	56	2,910	50	8.0 - 9.5	9.0	12.3	10.0	33.0	18.0
LT375/55R16/10	13565	33X15.50R16LT	83	3,750	65	10.0 - 13.0	10.0	15.5	12.0	32.8	22.0
LT315/75R16/8	15264	35X12.50R16LT	64	3,195	50	8.0-10.0	8.5	12.9	10.0	35.0	20.0
LT375/65R16/8	16564	36X15.50R16LT	93	3,750	50	10.0 - 13.0	11.0	15.7	12.2	35.8	22.0
LT325/80R16/8	17364	37X13.50R16LT	89	3,525	50	8.5 - 11.0	9.0	13.0	10.8	37.0	22.0
LT395/70R16/6	18564	38X15.50R16LT	97	3,415	35	12.0 - 13.0	12.0	16.0	12.2	37.8	22.0
33X12.50R17/8	13274		56	2,600	50	8.5 - 11.0	10.0	12.4	9.8	33.0	20.0
35X12.50R17/8	15274		64	3,000	50	8.5 - 11.0	10.0	12.9	10.2	35.0	20.0
37X13.50R17/8	17373		90	3,195	50	8.5 - 11.0	11.0	13.6	10.8	37.0	22.0
LT305/60R18/10	13285	33X12.50R18LT	65	3195	65	8.5-11	9.0	12.9	9.8	32.6	20.0
LT325/60R18/10	13385	33X13.50R18LT	85	3,525	65	9.0 - 12.0	9.5	13.3	10.8	33.2	22.0
LT375/50R18/10	13585	33X15.50R18LT	85	3,525	65	10.0 - 13.0	12.0	15.4	12.2	33.0	22.0
LT305/70R18/10	13285	35X12.50R18LT	71	3750	65	8 -10.0	9.0	12.3	9.8	35.0	20.0
LT325/65R18/10	15385	35X13.50R18LT	80	3,860	65	9.0 - 12.0	9.5	13.5	10.8	35.0	22.0
LT375/60R18/8	16584	36X15.50R18LT	94	3,640	50	10.0 - 13.0	11.0	15.5	12.2	35.8	22.0
37X13.50R18/8	17384		87	3,525	50	8.5 - 11.0	11.0	13.9	10.7	36.8	22.0
LT395/65R18/6	18583	38X15.50R18LT	101	3,415	35	11.0 - 14.0	12.0	15.7	12.2	37.8	22.0
40X13.50R18/8	10384		100	4,190	50	8.5 - 11.0	11.0	13.6	10.8	39.8	21.0
LT305/55R20/10	13225	33X12.50R20LT	63	3195	65	8.5-11.0	9.5	12.5	10.1	33.4	20.0
LT325/50R20/10	13325	33X13.50R20LT	75	3,085	6	9.0-12.0	10.0	13.2	10.8	33.0	22.0
35X12.50R20/10	15225		71	3195	65	8.5-11.0	10.0	12.5	9.8	34.6	20.0
35X13.50R20/10	15325		83	3,305	65	8.5 - 11.0	11.0	13.6	10.7	34.8	22.0
36X15.50R20/10	16525		92	3,750	65	11.0 - 13.0	12.0	15.3	12.2	35.8	22.0
38X15.50R20/8	18524		100	3,640	50	11.0 - 13.0	12.0	15.7	12.2	37.9	22.0
40X13.50R20/8	10324		98	3,970	50	8.5 - 11.0	11.0	13.6	10.8	39.8	21.0



NEW

NEW

NEW

NEW

DICK CEPEK



MUD COUNTRY *NEW TIRE*

SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
31X10.50R15/6	21053		47	2270	50	7.0-9.0	8.5	10.9	8.3	30.8	19.0
33X12.50R15/6	23253		57	2205	35	8.5-11.0	10.0	12.1	9.7	32.8	20.5
33X15.50R15/6	23553		87	2405	35	11.0-13.0	12.0	15.7	12.1	32.9	23.0
35X12.50R15/6	25253		68	2535	35	8.5-11.0	10.0	12.2	10.0	34.8	19.5
36X15.50R15/6	26553		96	3000	35	11.0-13.0	12.0	15.7	12.2	35.9	23.0
38X15.50R15/6	28553		102	3415	35	11.0-13.0	12.0	15.7	12.2	37.9	23.0
LT265/75R16/10	22065	32X10.50R16LT	54	3415	80	7.0-8.0	7.5	10.1	8.3	32.0	18.5
LT285/75R16/8	23164	32X11.50R16LT	57	3305	65	7.5-9.0	8.0	11.3	8.9	33.1	18.5
LT305/70R16/8	23264	33X1250R16LT	62	2910	50	8.0-9.5	9.0	12.0	9.8	33.1	19.0
LT375/55R16/10	23565	33X15.50R16LT	88	3750	65	10.0-13.0	12.0	15.4	11.8	32.4	23.0
LT315/75R16/8	25264	35X1250R16LT	68	3195	50	8.0-10.0	8.5	11.9	9.8	34.5	19.0
LT375/65R16/8	26564	36X15.50R16LT	97	3750	50	10.0-13.0	11.0	15.0	12.2	35.4	23.0
LT395/70R16/6	28564	38X15.50R16LT	102	3415	35	12.0-13.0	12.0	16.0	12.2	37.9	23.0
LT265/70R17/10	22075		55	3195	80	7.0-9.0	8.0	10.8	8.3	31.9	18.5
33X12.50R17/8	23274		64	2600	50	8.5-11.0	10.0	12.5	9.8	32.8	20.5
35X12.50R17/8	25274		80	3000	50	8.5-11.0	10.0	12.7	9.8	34.9	19.5
LT305/60R18/10	23285	33X12.50R18LT	65	3195	65	8.5-11.0	9.0	12.1	9.8	32.6	20.5
LT325/60R18/10	23385	33X13.50R18LT	82	3525	65	9.0-12.0	9.5	13.3	10.5	33.2	23.0
LT375/50R18/10	23585	33X15.50R18LT	91	3525	65	10.0-13.0	12.0	15.4	12.0	33.0	23.0
LT370/60R18/10	25285	35X12.50R18LT	71	3750	65	8.0-10.0	9.0	12.2	9.8	35.0	20.5
LT375/60R18/8	26584	36X15.50R18LT	99	3640	50	10.0-13.0	11.0	15.0	12.0	35.9	23.0
37X13.50R18/8	27384		94	3525	50	8.5-11.0	11.0	13.9	10.7	36.8	20.5
LT395/65R18/6	28583	38X15.50R18LT	106	3415	35	11.0-14.0	12.0	15.7	12.2	37.9	20.5
35X12.50R20/10	25225		71	3195	65	8.5-11.0	10.0	12.5	9.8	34.5	20.5
36X15.50R20/10	26525		98	3525	65	11.0-13.0	12.0	15.3	11.9	35.8	21.0
38X15.50R20/10	28524		105	3525	50	11.0-13.0	12.0	15.7	12.2	37.9	21.0
40X13.50R20/10	20324		101	3970	50	8.5-11.0	11.0	13.6	10.8	39.8	20.5

DICK CEPEK

CRUSHER NEW TIRE

OFF-ROAD RADIAL

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
31X10.50R15/6	31053		47	2,270	50	7.0 - 9.0	8.5	10.9	8.3	30.8	19.0
33X12.50R15/6	33253		56	2,205	35	8.5 - 11.0	10.0	12.1	9.7	32.8	20.5
35X12.50R15/6	35253		66	2,535	35	8.5 - 11.0	10.0	12.2	10.0	34.8	19.5
LT265/75R16/10	32065	32X10.50R16LT	53	3,415	80	7.0 - 8.0	7.5	10.1	8.3	32.0	18.5
LT285/75R16/8	33164	33X11.50R16LT	56	3,305	65	7.5 - 9.0	8.0	11.3	8.9	33.1	18.5
LT305/70R16/8	33264	33X12.50R16LT	61	2,910	50	8.0 - 9.5	9.0	12.0	9.8	33.1	19.0
LT315/75R16/8	35264	35X12.50R16LT	67	3,195	50	8.0-10.0	8.5	11.9	9.8	34.5	19.0
LT265/70R17/10	32075		53	3195	80	7.0 - 9.0	8.0	10.8	8.3	31.9	18.5
LT285/70R17/8	33174	33X11.50R17LT	57	3195	65	7.5 - 9.5	8.5	11.5	8.9	33.0	18.0
LT305/65R17/10	33275	33X12.50R17LT	62	3195	65	8.5 - 11.0	9.0	12.0	9.8	33.1	20.5
LT315/70R17/8	35274	35X12.50R17LT	68	3195	50	8.5 - 10.0	9.5	11.9	9.8	34.6	19.0
38X14.50R20/10	38425		94	3525	65	10.0 - 12.0	12.0	14.7	11.4	38.4	20.5



KEVLAR F-C

OFF-ROAD BIAS

TIRE SIZE	CODE #	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
36/16.50-16.5/8	10186	77	3,415	45 psi	9.75-14.0	12.0	15.8	13.0	35.8	19.0
38/15.50-16.5/6	10190	78	3,275	30 psi	9.75-12.0	12.0	14.5	11.0	37.2	19.0



FUN COUNTRY KEVLAR

OFF-ROAD BIAS

TIRE SIZE	CODE #	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
18.5/44-15/6	10150	94	2,855	30 psi	10.0 - 14.0	12.0	18.5	14.0	43.0	19.0



MICKEY THOMPSON



E.T. DRAG *A PROVEN DRAG STRIP WINNER*

TIRE SIZE	CODE #	WEIGHT	COMPOUND	SUGGESTED TUBE	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
22.0/8.0-13	3010	14	L8	9534	7	9.2	7.9	22.4	70
24.5/7.0-13	3012	15	L8	9534	7	9.5	6.9	24.5	77
24.5/8.0-13	3014	16	L8	9553	7	10.5	7.7	24.5	77
24.5/9.0-13	3016	16	L8	9553	7	10.9	8.8	24.5	77
20.0/6.0-14	3017	10	L8	-	6	7.3	6.0	20.8	65
20.0/8.0-14	3018	11	L8	-	6	9.2	8.0	20.3	64
24.5/8.0-14	3013	16	L8	9553	7	9.9	7.7	24.5	77
26.0/8.5-14	3020	18	L8	9553	8	10.2	8.2	26.0	82
28.0/9.0-14	3024	21	L8	9553	8	11.0	8.5	27.2	86
22.0/8.0-15	3019	14	L8	-	7	8.6	7.9	22.4	70
24.5/8.0-15	3015	17	L8	9553	8	9.6	7.7	24.5	77
26.0/8.5-15	3052	19	L8	9553	8	9.9	8.1	25.9	82
26.0/10.0-15	3053	22	L8	9553	10	11.6	9.6	26.0	82
26.0/10.0-15S	3053C	19	L4	9553	10	11.5	9.8	26.5	83
28.0/9.0-15	3054	22	L8	9553	8	10.8	8.6	27.3	86
28.0/10.5-15	3055	23	M5	9553	10	11.7	10.0	28.1	88
28.0/10.5-15C	3055C	23	L4	9553	10	12.0	10.0	28.1	88
28.0/10.5-15S	3055S	24	M5	9553	10	11.7	10.0	28.1	88
28.0/10.5-15W	3055W	26	M5	9555	10	13.1	10.9	28.1	88
28.0/11.5-15	3057	26	M5	9555	10	12.9	11.0	28.0	88
28.0/11.5-15C	3057C	22	L4	9555	10	12.9	11.0	28.1	88
29.5/9.0R15 RADIAL	3056R	23	R1	Tubeless	10	11.5	8.5	29.5	92
29.5/9.0-15ST	3056ST	22	M5	9553	8	11.4	8.9	29.3	92
29.5/9.0-15	3056	22	L8	9553	8	11.4	8.9	29.3	92
29.5/10.5-15	3062	25	M5	9555	10	13.1	10.2	29.9	94
29.5/10.5-15S	3062S	27	M5	9555	10	13.2	10.2	29.9	94
29.5/10.5-15W	3062W	30	M5	9555	10	13.6	11.2	29.6	93
29.5/11.5-15	3064	27	M5	9555	10	13.6	11.1	29.9	94
29.5/13.5-15	3065	29	M5	9555	12	16.0	13.1	30.2	95
30.0/9.0-15	3066	22	L8	9555	10	12.5	8.8	30.0	94
30.0/9.0R15 RADIAL	3066R	23	R1	Tubeless	10	12.5	9.0	29.7	93
31.0/10.5-15W	3068W	33	M5	9555	10	14.5	10.8	31.3	99
31.0/13.0-15	3072	32	M5	9558	12	15.7	13.0	31.0	98
31.25/12.2-15W	3073W	29	L8	9558	12	15.8	13.2	31.5	98
31.25/12.2R15W	3073R	30	R1	Tubeless	14	16.3	13.5	31.9	100
32.0/14.0-15	3074	33	L8	9558	14	17.2	14.2	31.8	100
32.0/14.0R15 RADIAL	3074R	32	R1	Tubeless	14	17.4	14.0	32.3	101.75
32.0/14.0-15S	3074S	35	L8	9558	14	17.1	14.2	32.2	100
32.0/14.0-15SS	3074SS	36	L8	9558	14	17.1	14.2	32.2	100
32.0/14.5-15	3075	38	L8	9558	14	18.0	14.8	32.5	103
32.0/16.0-15S	3076S	35	L8	9558	15	18.5	15.8	32.0	101
32.0/16.0-15SS	3076SS	42	L8	9558	15	18.5	15.8	32.0	101

MICKEY THOMPSON

E.T. DRAG *continued* A PROVEN DRAG STRIP WINNER

TIRE SIZE	CODE #	WEIGHT	COMPOUND	SUGGESTED TUBE	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
33.0/10.5-15W	3069W	33	M5	9558	10	14.5	11.2	32.9	103
33.0/14.5R15	3078R	35	R1	Tubeless	14	17.6	14.5	33.0	103
33.0/15.0-15	3079	37	L4	9558	14	18.1	14.8	33.6	105
33.0/15.0-15SS	3079SS	40	L8	9558	14	18.1	14.8	33.6	105
33.0/16.5-15	3084	39	L4	9558	15	20.0	16.7	33.5	105
33.0/16.5-15S	3084S	41	L8	9558	15	20.0	16.7	33.5	105
33.0/17.0-15	3085	36	L8	9558	16	21.0	16.6	32.1	101
33.0/17.0-15SS	3085SS	42	M5	9558	16	21.0	16.6	32.1	101
33.0/17.0-15	3088	36	L4	9558	16	21.0	16.6	32.1	101
33.5/16.5-16	3185	42	M5	9558	16	20.8	16.5	33.7	106
33.5/16.5-16D	3185D	42	L4	9558	16	20.8	16.5	33.7	106
34.5/17.0-16	3186	45	M5	N/A	16	21.0	17.0	35.0	110
34.5/17.0-16	3187	45	M7	N/A	16	21.0	17.0	35.0	110
36.0/17.0-16	3188	50	M7	N/A	16	21.5	17.3	36.0	113



NEW
NEW

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.

MOTORCYCLE DRAG TIRES

M/T IS NUMBER ONE IN MOTORCYCLE DRAG RACING FOR OVER 10 YEARS STRAIGHT!

TIRE SIZE	CODE #	WEIGHT	COMPOUND	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
2.50/2.75-18	3210	6	NA	3.0	3.1	1.7	23.5	74
25.0/5.5-18	3220	11	L7	5.0	6.1	5.2	25.8	81
26.0/7.0-17	3221	13	M5	6.5	7.4	6.5	25.7	81
25.0/7.0-18	3222	12	L7	6.5	7.2	6.6	25.9	81
190/50VR17	3295	11	B2	6.0	7.4	7.4	25.1	78
190/50ZR17	3299	13	B1	6.0	7.4	7.4	24.8	78
26.0/10.0-15	3053M	19	L7	9.0	11.0	9.8	26.0	82
29.0/11.0-15	3064M	23	M7	10.0	13.1	10.8	28.7	89
29.0/13.0-15	3065M	26	M7	12.0	15.0	12.5	28.5	90
31.0/14.0-15	3073M	34	L7	13.0	16.8	13.6	31.0	97
27.0/10.0-16M	3158M	20	L7	9.0	11.6	10.0	27.0	85



NEW

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.

MICKEY THOMPSON



E.T. DRAG SPORT COMPACT *THE NUMBER ONE SPORT COMPACT DRAG TIRE!*

TIRE SIZE	CODE #	WEIGHT	COMPOUND	SUGGESTED TUBE	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
22.0/8.0-13	3010	14	L8	9534	7.0	9.2	7.9	22.4	70
24.5/7.0-13	3012	15	L8	9534	7.0	9.5	6.9	24.5	77
24.5/8.0-13	3014	16	L8	9553	7.0	10.5	7.7	24.5	77
24.5/9.0-13	3016	16	L8	9553	7.0	10.9	8.8	24.5	77
20.0/6.0-14	3017	10	L8	-	6.0	7.3	6.0	20.8	65
20.0/8.0-14	3018	11	L8	-	6.0	9.2	8.0	20.3	64
24.5/8.0-14	3013	16	L8	9553	7.0	9.9	7.7	24.5	77
26.0/8.5-14	3020	18	L8	9553	8.0	10.2	8.2	26.0	82
28.0/9.0-14	3024	21	L8	9553	8.0	11.0	8.5	27.2	86
22.0/8.0-15	3019	14	L8	-	7.0	8.6	7.9	22.4	70
24.5/8.0-15	3015	17	L8	9553	8.0	9.6	7.7	24.5	77
26.0/10.0-15C	3053C	19	L4	9553	10.0	11.5	9.8	26.5	83
28.0/10.5-15C	3055C	23	L4	9553	10.0	12.0	10.0	28.1	88
28.0/11.5-15C	3057C	22	L4	9555	10.0	12.9	11.0	28.1	88
29.5/9.0-15	3056	22	L8	9553	8.0	11.4	8.9	29.3	92

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.



E.T. STREET *WORLD'S FASTEST D.O.T. CLASS RACE TIRE*

TIRE SIZE	CODE #	WEIGHT	COMPOUND	SUGGESTED TUBE	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
26X10.50-15LT	3752	20	M5	9553	8.0	10.5	8.3	26.1	82
26X11.50-15LT	3753	22	M5	9553	10.0	12.0	9.8	26.3	82
27X10.50-15LT	3758	22	M5	9553	8.0	10.6	8.9	27.0	85
28X11.50-15LT	3754	22	M5	9553	8.0	11.1	8.6	27.6	87
28X12.50-15LT	3755	24	M5	9553	10.0	12.6	10.0	28.1	88
28X13.50-15LT	3757	28	M5	9555	10.0	13.2	11.0	28.0	88
30X12.50-15LT	3762	26	M5	9555	10.0	13.3	10.2	30.0	94
30X13.50-15LT	3763	31	M5	9555	10.0	13.7	11.1	30.0	94
31X14.50-15LT	3768	33	M5	9555	10.0	14.5	10.8	31.3	99
31X16.50-15LT	3772	34	M5	9558	12.0	15.5	12.4	31.5	99
32X17.50-15LT	3774	37	M5	9558	14.0	17.7	14.2	32.2	101
33X18.50-15LT	3780	43	M5	9558	14.0	18.8	15.8	33.3	104
26X10.50-16LT	3792	22	M5	9553	9.0	10.3	8.4	25.9	82
26X11.50-16LT	3793	24	M5	9553	10.0	10.8	9.7	26.2	82
27X10.50-16LT	3794	20	M5	9553	8.0	10.4	8.7	27.0	85
28X11.50-16LT	3796	24	M5	9553	8.0	10.7	8.7	28.0	88
28X12.50-16LT	3797	25	M5	9553	10.0	12.1	10.0	28.0	88
26X11.50-17LT	3743	23	M5	-	11.0	11.1	9.5	26.5	83

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.
CAUTION: It is NOT RECOMMENDED that RADIAL and NON-RADIAL Tires be mixed on the same Vehicle.

MICKEY THOMPSON

E.T. STREET RADIAL *WORLD'S FASTEST STREET RADIAL!*

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	COMPOUND	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
P235/60R15	3752R	26 X 9.50R15	26	R2	7.0 - 8.5	8	9.5	8.0	26	82
P275/50R15	3753R	26 X 11.50R15	30	R2	9.0 - 11.0	10	11.3	10.0	26	82
P255/60R15	3756R	27 X 10.50R15	31	R2	7.0 - 9.0	8	10.7	8.8	27	85
P275/60R15	3754R	28 X 11.50R15	32	R2	8.0 - 11.0	8	11.1	9.2	28	87
P325/50R15	3757R	28 X 13.50R15	36	R2	10.0 - 12.0	10	13	11.0	28	87
P295/65R15	3762R	30 X 12.50R15	38	R2	9.0 - 12.0	10	12.4	10.0	30	94
P315/60R15	3763R	30 X 13.50R15	40	R2	10.0 - 12.0	10	13.4	11.0	30	94
P255/50R16	3793R	26 X 10.50R16	28	R2	8.5 - 10.0	10	10.3	9.7	26	82
P275/40R17	3743R	26 X 11.50R17	28	R2	9.0 - 10.0	9	11	10.2	26	82



E.T. STREET RADIAL *OPTIMIZED FOR MODERN SPORTS CARS & SPORT COMPACTS*

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	COMPOUND	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
P205/50R15	3750R	23X8.0R15	22	R2	5.5 - 7.5	6.5	8.42	7.6	23.13	73.0
P225/50R15	3751R	24X9.0R15	23	R2	6.0 - 8.0	7.0	9.44	8.2	23.98	75.3
P295/50R16	3794R	28X11.50R16	33	R2	8.0 - 10.0	9.5	12.09	10.8	27.69	86.9
P315/45R16	3795R	27X12.50R16	34	R2	10.0 - 12.0	11.0	12.61	11.2	27.19	85.5
P315/35R17	3744R	28X11.50R17	33	R2	9.5 - 11.0	10.0	11.57	10.6	27.19	85.4
P295/45R17	3745R	26X12.50R17	31	R2	11.0 - 12.0	11.0	12.69	11.7	25.78	81.0
P305/35R18	3785R	27X12.50R18	31	R2	10.0 - 11.0	12.0	12.50	11.5	26.39	82.9
P345/35R18	3788R	28X13.50R18	35	R2	11.0 - 13.0	12.0	13.89	12.8	27.49	86.3



E.T. Front

TIRE SIZE	CODE #	WEIGHT	PICTURE	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
22.0/2.5-17	3004	4	C	2.5	2.5	2.7	1.5	22.0	67
22.5/4.5-15	3005	7	A	3.5 - 5.0	4.0	5.1	4.1	22.5	71
24.0/4.5-15	3006	11	A	3.5 - 5.0	4.0	6.4	4.8	23.8	75
25.0/4.5-15	3003	11	A	3.5 - 5.0	4.0	6.7	5.0	25.3	79
26.0/4.5-15	3007	12	A	3.5 - 5.0	4.0	6.8	4.9	25.9	81
27.5/4.5-15	3009	13	A	3.5 - 5.0	4.0	7.0	5.0	27.3	86
28.0/4.5-15	3002	13	A	3.5 - 4.5	4.0	7.2	5.1	28.0	88
29.0/4.5-15	3008**	12	B	3.5 - 5.0	4.0	7.3	4.5	28.7	90



** Not Acceptable for Land Speed Record use.

MICKEY THOMPSON



E.T. JR. #1 IN JR. DRAG RACING TIRES

TIRE SIZE	CODE #	WEIGHT	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	CIRCUMFERENCE
18/8-8	3621	5.8	M2	8	10.5	7.3	18	55
18/8.5-8	3623	-	-	-	-	-	-	-
19/8-10	3644	9.2	M2	8	9.5	7.2	19.5	61

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.



SPORTSMAN S/R A MUST FOR ANY STREET ROD OR STREET MACHINE BUILDER

TIRE SIZE	CODE #	WEIGHT	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
24X5.00R15LT	6651	15.0	3.5 - 4.5	4	5.8	4.5	24.0
26X6.00R15LT	6652	20.0	4.0 - 5.0	4	6.5	5.7	26.0
26X8.00R15LT	6650	20.3	5.0 - 7.0	6	8.5	7.0	26.1
26X10.00R15LT	6653	23.1	7.0 - 9.0	8	10.3	8.8	26.1
26X12.00R15LT	6654	25.5	8.0 - 10.0	10	12.0	10.6	26.1
NEW 28X10.00R15LT	6640	27.0	7.0 - 8.5	8	10.3	8.7	28.0
NEW 28X12.00R15LT	6641	31.0	8.5 - 10.0	10	12.1	10.4	28.0
NEW 29X15.00R15LT	6642	41.0	10.0 - 13.0	12	15.0	13.0	29.0
29X18.00R15LT	6655	49.0	14.0 - 16.0	14	17.6	15.8	29.0
NEW 30X12.00R15LT	6643	36.0	8.5 - 10.0	10	12.6	10.2	30.0
NEW 31X16.00R15LT	6644	47.0	12.0 - 14.0	12	16.0	13.5	31.0
31X18.00R15LT	6656	50.0	14.0 - 16.0	14	17.9	15.7	31.0
33X22.00R15LT	6657	59.0	15.0 - 18.0	15	20.0	17.8	32.0
24X5.00R18LT	6681	TBD	4.0 - 4.5	4	5.2	4.5	24.0
26X6.00R18LT	6682	17.6	4.5 - 5.5	5	6.0	5.7	26.0
26X8.00R18LT	6680	TBD	5.5 - 7.0	6	8.0	7.5	26.0
26X10.00R18LT	6683	TBD	8.0 - 9.0	9	10.0	9.2	26.0
26X12.00R18LT	6684	TBD	8.0 - 10.0	10	12.0	10.5	26.0
NEW 28X10.00R18LT	6670	28.0	7.5 - 9.0	8	9.8	8.7	27.9
NEW 28X12.00R18LT	6671	33.0	9.0 - 10.0	10	11.6	10.6	28.0
29X18.00R18LT	6685	49.0	15.0 - 16.0	15	17.2	15.5	29.0
NEW 30X12.00R18LT	6672	36.0	9.0 - 11.0	10	12.3	10.2	29.9
31X18.00R18LT	6686	50.0	14.0 - 16.0	15	17.6	15.5	31.0
33X22.00R18LT	6687	59.0	15.0 - 18.0	16	19.3	17.8	32.0
NEW 29X15.00R20LT	6620	41.0	13.0 - 14.0	14	14.7	13.0	29.0
NEW 31X16.00R20LT	6621	47.0	12.0 - 14.0	14	15.7	13.5	31.0
29X18.00R20LT	6625	46.0	15.0 - 16.0	16	17.2	15.5	29.0
31X18.00R20LT	6626	50.0	15.0 - 16.0	16	17.3	15.7	31.1
33X22.00R20LT	6627	58.0	16.0 - 18.0	17	18.9	17.8	32.0



MICKEY THOMPSON

SPORTSMAN *WIDEST HIGH PERFORMANCE STREET LEGAL TIRE*

TIRE SIZE	CODE #	WEIGHT	SUGGESTED TUBE	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
29X12.50-15LT	1557	34		8.0 - 11.0	10	13.0	10.6	29
29X15.50-15LT	1558	35	9558	10.0 - 13.0	12	15.4	12.9	29
29X18.50-15LT	1559	40	9558	14.0 - 16.0	14	17.4	15.5	29
31X16.50-15LT	1560	41	9558	12.0 - 14.0	12	15.7	12.5	30
31X18.50-15LT	1562	45	9558	14.0 - 16.0	14	17.6	14.4	31
33X19.50-15LT	1564	47	9558	14.0 - 16.0	14	18.0	14.3	32
33X21.50-15LT	1565	52	9558	15.0 - 18.0	15	20.2	16.8	32



SPORTSMAN PRO *WIDEST HIGH PERFORMANCE STREET LEGAL TIRE*

TIRE SIZE	CODE #	WEIGHT	SUGGESTED TUBE	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
26X9.50-15LT	6540	23	9553	7.0 - 8.0	8	9.9	8.0	26
26X10.50-15LT	6542	23	9553	7.0 - 10.0	8	10.4	8.0	26
26X12.50-15LT	6544	26	9553	8.0 - 11.0	10	11.9	10.0	26
28X10.50-15LT	6546	23	9553	7.0 - 9.0	8	11.2	8.3	28
28X12.50-15LT	6548	26	9553	8.0 - 11.0	10	13.1	10.4	28
29X12.50-15LT	6557	27	9555	8.0 - 11.0	10	13.0	10.0	29
29X15.50-15LT	6558	32	9558	10.0 - 13.0	12	15.3	12.7	29
29X18.50-15LT	6559	37	9558	14.0 - 16.0	14	17.6	15.5	29
31X16.50-15LT	6560	34	9558	12.0 - 14.0	12	15.7	12.2	31
31X18.50-15LT	6562	37	9558	14.0 - 16.0	14	17.5	14.3	31
33X19.50-15LT	6564	39	9558	14.0 - 16.0	14	18.0	14.5	32
33X21.50-15LT	6565	44	9558	15.0 - 18.0	15	19.6	16.6	32



SPORTSMAN FRONT

NARROW FRONT TIRE THAT COMPLIMENTS OUR SPORTSMAN™ AND SPORTSMAN PRO® TIRE LINES

TIRE SIZE	CODE #	WEIGHT	SUGGESTED TUBE	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
26X7.50-15	1572	16	-	3.5 - 6.5	4	6.3	4.8	26
26X7.50-15 8 PLY	1573	19	-	3.5 - 6.5	4	6.3	4.8	26
28X7.50-15	1574	20	-	3.5 - 6.5	4	6.9	5.5	28
26X8.50-15	1575	22	-	4.5 - 7.0	6	8.3	6.7	27



CAUTION: It is NOT RECOMMENDED that RADIAL and NON-RADIAL Tires be mixed on the same Vehicle.

SPORTSMAN 'I' *GREAT FOR STREET CLASS DRAG RACING AND CLASSIC GOOD LOOKS*

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
P215/50D13	1525		18	5.5 - 8.0	7.0	8.6	7.4	22
P235/50D13	1530		18	6.0 - 9.0	7.0	9.0	8.4	22
P245/50D13	1532		21	6.5 - 9.0	7.0	9.5	8.8	23
G60-15	1566	255/60-15	30	6.0 - 8.0	8.0	10.4	7.8	27
L60-15	1568	275/60-15	34	7.0 - 10.0	10.0	12.2	10.0	28
N50-15	1578	345/50-15	37	8.0 - 11.0	10.0	13.0	11.8	28



MICKEY THOMPSON



INDY PROFILE

FOR THE TRUE HIGH PERFORMANCE LOOK OF THE MUSCLE CAR ERA THIS IS THE PERFECT TIRE CHOICE

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
F70-14	1022	215/70-14	27	5.5 - 7.0	6.0	8.5	6.0	26
L60-14	1036	295/60-14	35	7.0 - 10.0	10.0	12.3	9.5	28
N50-14	1044	345/50-14	38	9.0 - 12.0	10.0	13.2	11.8	27
F70-15	1052	215/70-15	27	5.5 - 7.0	6.0	8.5	6.0	27
G70-15	1054	235/70-15	31	5.5 - 8.0	6.0	9.2	6.5	28
H50-15	1074	295/50-15	34	7.0 - 10.0	10.0	12.3	10.0	26



INDY PROFILE S/S

FOR THE TRUE HIGH PERFORMANCE LOOK OF THE MUSCLE CAR ERA THIS IS THE PERFECT TIRE CHOICE

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
G60-14	7034	255/60-14	31	6.5 - 9.0	8.0	10.4	8.0	25
G60-15	7066	255/60-15	30	6.0 - 8.0	8.0	10.2	8.0	26
L60-15	7068	275/60-15	37	7.0 - 10.0	10.0	12.3	9.5	28
N50-15	7076	345/50-15	40	8.0 - 11.0	10.0	14.1	11.8	28



BAJA RADIAL MTX POLYESTER PLY/STREET BELTED, OUTLINED WHITE LETTERS

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
P225/75R15	5549	28X9.50R15	27	1,874	35 psi	6.0 - 7.0	7.0	9.0	6.4	28	13.5
30X9.50R15/6	5550	LT235/75R15	36	1,985	50 psi	6.5 - 8.5	7.5	9.3	7.0	29	16.5
31X10.50R15/6	5551	LT255/75R15	40	2,270	50 psi	7.0 - 9.0	8.5	10.5	7.9	30	16.5
31X11.50R15/6	5552		45	2,340	50 psi	8.0 - 10.0	9.0	10.8	8.4	31	18
32X11.50R15/6	5553		45	2,535	50 psi	8.0 - 10.0	9.0	10.8	8.6	32	18
33X12.50R15/6	5554		52	2,205	35 psi	8.5 - 11.0	10.0	12.4	9.3	32	18
35X12.50R15/6	5556		62	2,535	35 psi	8.5 - 10.0	10.0	13.0	10.0	35	18
LT265/75R16/8	5560	32X10.50R16LT	52	3,000	65 psi	7.0 - 8.0	7.5	10.4	7.4	32	16
LT225/75R16/8	5561	28X9.50R16LT	37	2,335	65 psi	6.0 - 7.0	6.0	8.7	6.4	29	13.5
LT285/75R16/8	5563	33X11.50R16LT	54	3,305	65 psi	7.0 - 9.0	8.0	11.4	9.0	33	16.5
LT235/85R16/10	5564	32X9.50R16LT	40	3,042	80 psi	6.0 - 7.0	6.5	9.6	6.2	32	17
LT305/70R16/8	5566	33X12.50R16LT	56	2,910	50 psi	8.0 - 10.0	10.0	11.7	9.8	33	18
LT315/75R16/8	5568	35X12.50R16LT	57	3,195	50 psi	8.0 - 10.0	10.0	12.9	10.3	35	18
P265/70R17	5572	32X10.50R17	40	2,535	35 psi	7.0 - 9.0	8.0	10.9	8.4	32	13.5
33X12.50R17/8	5574		54	2,600	50 psi	7.0 - 10.0	8.0	11.7	10.0	33	19

MICKEY THOMPSON

BAJA ATZ PLUS RADIAL *POPULAR SIZES AVAILABLE FOR TODAY'S MODERN VEHICLES!*

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
30X9.50R15/6	5150		36	1985	50 psi	6.5 - 8.5	7.50	9.30	7.30	29.3	16.5
31X10.50R15/6	5151		40	2270	50 psi	7.0 - 9.0	8.50	10.50	8.20	30.3	16.5
32X11.50R15/6	5152		44	2535	50 psi	8.0 - 10.0	9.00	11.40	9.00	31.5	17.0
33X12.50R15/6	5153		50	2205	35 psi	8.5 - 11.0	10.00	12.50	9.60	32.5	17.0
35X12.50R15/6	5154		59	2535	35 psi	8.5 - 11.0	10.00	12.50	10.20	34.5	17.0
LT225/75R16/10	5160	28X9.50R16	38	2680	80 psi	6.0 - 7.0	6.00	8.90	6.90	29.4	16.5
LT245/75R16/10	5161	31X9.50R16	43	3042	80 psi	6.5 - 7.5	7.00	9.60	7.40	30.5	16.5
LT235/85R16/10	5164	32X9.50R16	43	3042	80 psi	6.0 - 7.0	6.50	9.40	6.70	31.8	16.5
LT265/75R16/10	5162	32X10.50R16	46	3415	80 psi	7.0 - 8.0	7.50	10.60	7.80	31.8	16.5
LT285/75R16/8	5163	33X11.50R16	51	3305	65 psi	7.5 - 9.0	8.00	11.50	8.80	32.9	17.0
LT305/70R16/8	5165	33X12.50R16	54	2910	50 psi	8.0 - 9.5	9.00	12.20	9.70	33.0	17.0
LT315/75R16/8	5166	35X12.50R16	62	3195	50 psi	8.0 - 10.0	8.50	12.90	9.80	34.8	17.0
LT245/70R17/10	5170	31X9.50R17	43	3000	80 psi	6.5 - 8.0	7.00	9.80	7.30	30.6	16.5
LT265/70R17/10	5171	32X10.50R17	50	3195	80 psi	7.0 - 8.5	8.00	10.70	8.50	31.6	16.5
33X12.50R17/8	5173		55	2600	50 psi	8.5 - 11.0	10.00	12.50	9.60	32.5	17.0
LT285/70R17/8	5174	33X11.50R17	52	3195	65 psi	7.5 - 9.0	8.50	11.50	9.00	32.8	17.0
LT315/70R17/8	5175	35X12.50R17	60	3195	50 psi	8.5 - 10.0	9.50	12.90	9.90	34.9	17.0
LT275/65R18/10	5180	32X11.50R18	52	3415	80 psi	7.5 - 9.5	8.00	11.00	8.80	32.1	16.0



BAJA ATZ RADIAL *POPULAR SIZES AVAILABLE FOR TODAY'S OFF-ROAD VEHICLES!*

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
TRADITIONAL											
33X12.50R15/6	5353		52	2205	35	8.5 - 11.0	10.00	12.40	9.80	32.6	20
LT265/75R16/10	5362	32X10.50R16	48	3415	80	7.0 - 8.0	7.50	10.50	8.10	31.8	18
LT285/75R16/8	5363	33X11.50R16	57	3305	65	7.5 - 9.0	8.00	11.30	9.20	32.8	20
LT305/70R16/8	5365	33X12.50R16	57	2910	50	8.0 - 9.5	9.00	12.30	10.00	32.9	18
LT315/75R16/8	5366	35X12.50R16	65	3195	50	8.0 - 10.0	8.50	12.90	10.00	34.5	20
LT265/70R17/10	5371	32X10.50R17	51	3195	80	7.0 - 8.5	8.00	10.70	8.40	31.7	18
LT285/70R17/8	5374	33X11.50R17	55	3195	65	7.5 - 9.0	8.50	11.40	9.10	32.8	18
LT305/65R17/10	5373	33X12.50R17	59	3195	65	8.5 - 11.0	9.00	12.20	9.80	32.6	20
35X12.50R17/8	5375		67	3000	50	8.5 - 11.0	10.00	12.90	10.20	34.9	20
LT275/70R18/10	5388	33X11.50R18	56	3640	80	7.0 - 9.0	8.00	11.00	8.80	33.3	18
LT305/60R18/10	5387	33X12.50R18	65	3195	65	8.5 - 11.0	9.00	12.10	9.80	32.6	20
LT305/70R18/10	5389	35X12.50R18	71	3750	65	8.0 - 10.0	9.00	12.20	9.80	35.0	20
LT305/55R20/10	5328	33X12.50R20	66	3195	65	8.5 - 11.0	8.50	12.50	10.10	33.4	20
35X12.50R20/10	5329		71	3195	65	8.5 - 11.0	10.00	12.50	9.80	34.5	20
SPECIALTY SIZES											
33X15.50R15/6	5155		83	2,405	35	11.0 - 13.0	12.0	15.7	12.1	32.9	20.5
36X15.50R15/6	5156		92	3,000	35	11.0 - 13.0	12.0	15.6	12.2	35.7	20.5
38X15.50R15/6	5157		97	3,415	35	11.0 - 13.0	12.0	15.7	12.2	37.8	20.5
LT375/55R16/10	5167	33X15.50R16LT	83	3,750	65	10.0 - 13.0	10.0	15.5	12.0	32.8	20.5
LT375/65R16/8	5168	36X15.50R16LT	93	3,750	50	10.0 - 13.0	11.0	15.7	12.2	35.7	20.5
LT395/70R16/6	5169	38X15.50R16LT	97	3,415	35	12.0 - 13.0	12.0	16.0	12.2	37.9	20.5
LT325/60R18/10	5181	33X13.50R18LT	85	3,525	65	9.0 - 12.0	9.5	13.3	10.8	33.2	19.0



MICKEY THOMPSON



BAJA ATZ RADIAL *continued* POPULAR SIZES AVAILABLE FOR TODAY'S OFF-ROAD VEHICLES!

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
SPECIALTY SIZES											
LT375/50R18/10	5182	33X15.50R18LT	85	3,525	65	10.0 - 13.0	12.0	15.4	12.2	33.0	20.5
LT325/65R18/10	5183	35X13.50R18LT	81	3,860	65	9.0 - 12.0	9.5	13.5	10.8	34.8	19.0
LT375/60R18/8	5184	36X15.50R18LT	94	3,640	50	10.0 - 13.0	11.0	15.5	12.2	35.7	20.5
37X13.50R18/8	5185		89	3,525	50	8.5 - 11.0	11.0	13.9	10.7	36.8	21.0
LT395/65R18/6	5186	38X15.50R18LT	101	3,415	35	11.0 - 14.0	12.0	15.7	12.2	37.8	20.5
40X13.50R18/8	5187		100	4,190	50	8.5 - 11.0	11.0	13.6	10.8	39.8	20.5
LT325/50R20/10	5120	33X13.50R20LT	75	3,085	65	10.0	10.0	13.2	10.8	33.0	19.0
35X13.50R20/10	5121		83	3,305	65	8.5 - 11.0	11.0	13.6	10.7	34.8	19.0
36X15.50R20/10	5122		92	3,750	65	11.0 - 13.0	12.0	15.3	12.2	35.8	19.0
38X15.50R20/8	5123		100	3,640	50	11.0 - 13.0	12.0	15.7	12.2	37.9	19.0
40X13.50R20/8	5124		98	3,970	50	8.5 - 11.0	11.0	13.6	10.8	39.8	20.5

SPECIALTY LIGHT TRUCK SIZES FEATURE 3 PLY SIDEWALL AND 6 PLY TREAD FOR ADDED STRENGTH AND PUNCTURE RESISTANCE



BAJA MTZ RADIAL

AVAILABLE FOR TODAY'S DEMANDING OFF-ROAD VEHICLES!

POPULAR SIZES

TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
TRADITIONAL											
31X10.50R15/6	5251		47	2270	50	7.0 - 9.0	8.5	10.9	8.3	30.8	19.0
33X12.50R15/6	5253		56	2205	35	8.5 - 11.0	10.0	12.1	9.7	32.8	20.5
35X12.50R15/6	5254		66	2535	35	8.5 - 11.0	10.0	12.2	10.0	34.8	19.5
LT265/75R16/10	5262	32X10.50R16	53	3415	80	7.0 - 8.0	7.5	10.1	8.3	32.0	18.5
LT285/75R16/8	5263	33X11.50R16	56	3305	65	7.5 - 9.0	8.0	11.3	8.9	33.1	18.5
LT305/70R16/8	5265	33X12.50R16	61	2910	50	8.0 - 9.5	9.0	12.0	9.8	33.1	19.0
LT315/75R16/8	5266	35X12.50R16	67	3195	50	8.0 - 10.0	8.5	11.9	9.8	33.5	19.0
LT265/70R17/10	5271	32X10.50R17	53	3195	80	7.0 - 9.0	8.0	10.8	8.3	31.9	18.5
33X12.50R17/8	5273		63	2600	50	8.5 - 11.0	10.0	12.5	9.8	32.8	20.5
LT315/70R17/8	5275	35X12.50R17	68	3195	50	8.0 - 11.0	8.0	11.9	9.8	34.6	19.0
SPECIALTY SIZES											
33X15.50R15/6	5255		79	2,405	35	11.0 - 13.0	12.0	15.7	12.1	32.9	23.0
36X15.50R15/6	5256		87	3,000	35	11.0 - 13.0	12.0	15.7	12.2	35.9	23.0
38X15.50R15/6	5257		92	3,415	35	11.0 - 13.0	12.0	15.7	12.2	37.9	23.0
LT375/55R16/10	5267	33X15.50R16LT	79	3,750	65	10.0 - 13.0	12.0	15.4	11.8	32.4	23.0
LT375/65R16/8	5268	36X15.50R16LT	88	3,750	50	10.0 - 13.0	11.0	15.0	12.2	35.4	23.0
LT395/70R16/6	5269	38X15.50R16LT	92	3,415	35	12.0 - 13.0	12.0	16.0	12.2	37.9	23.0
LT325/60R18/10	5281	33X13.50R18LT	74	3,525	65	9.0 - 12.0	9.5	13.3	10.5	33.2	20.5
LT375/50R18/10	5282	33X15.50R18LT	81	3,525	65	10.0 - 13.0	12.0	15.4	12.2	33.0	23.0
LT325/65R18/10	5283	35X13.50R18LT	78	3,860	65	9.0 - 12.0	9.5	13.5	10.6	34.8	20.5
LT375/60R18/8	5284	36X15.50R18LT	89	3,640	50	10.0 - 13.0	11.0	15.0	12.0	35.9	23.0
37X13.50R18/8	5285		86	3,525	50	8.5 - 11.0	11.0	13.9	10.7	36.8	20.5
LT395/65R18/6	5286	38X15.50R18LT	96	3,415	35	11.0 - 14.0	12.0	15.7	12.2	37.9	23.0
36X15.50R20/10	5222		88	3,525	65	11.0 - 13.0	12.0	15.3	12.2	35.8	21.0
38X15.50R20/8	5223		99	3,525	50	11.0 - 13.0	12.0	15.7	12.2	37.9	23.0

SPECIALTY LIGHT TRUCK SIZES FEATURE 3 PLY SIDEWALL AND 6 PLY TREAD FOR ADDED STRENGTH AND PUNCTURE RESISTANCE

MICKEY THOMPSON

BAJA CLAW RADIAL *THE ORIGINAL EXTREME TERRAIN TIRE!*



TIRE SIZE	CODE #	EQUIVALENT SIZE	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
TRADITIONAL											
31X10.50R15/6	5751		41	2,250	50	7.0 - 9.0	8.5	10.5	8.3	31.0	20.0
33X12.50R15/6	5754		53	2,225	35	8.5 - 11.0	10.0	12.5	10.0	33.0	20.5
33X15.50R15/6	5755		79	2,405	35	11.0 - 13.0	12.0	15.7	11.9	32.9	23.0
35X12.50R15/6	5756		63	2,535	35	8.5 - 10.0	10.0	12.9	10.3	34.9	20.5
LT305/70R16/8	5766	33X12.50R16LT	56	2,910	50	8.0 - 9.5	9.0	11.7	10.0	33.0	18.5
LT315/75R16/8	5768	35X12.50R16LT	62	3,195	50	8.0 - 10.0	8.5	12.5	10.7	34.8	20.0
LT395/70R16/6	5760	38X15.50R16LT	92	3,415	35	12.0 - 13.0	12.0	16.0	12.0	37.9	23.0
33X12.50R17/8	5774		57	2,600	50	8.5 - 11.0	10.0	12.5	10.0	32.5	20.0
35X12.50R17/8	5776		63	3,000	50	8.5 - 11.0	10.0	12.7	10.7	34.9	20.0
SPECIALTY SIZES											
36X15.50R15/6	5757		87	3,000	35	11.0 - 13.0	12.0	15.7	12.0	35.9	23.0
37X13.50R15/6	5759		82	3,000	35	8.5 - 11.0	11.0	13.6	10.8	36.9	22.5
38X15.50R15/6	5750		92	3,415	35	11.0 - 13.0	12.0	15.7	12.2	37.9	23.0
LT375/55R16/10	5765	33X15.50R16LT	79	3,750	65	10.0 - 13.0	12.0	15.4	11.8	32.4	23.0
LT375/65R16/8	5767	36X15.50R16LT	88	3,750	50	10.0 - 13.0	11.0	15.0	12.0	35.4	23.0
LT325/80R16/8	5769	37X13.50R16LT	83	3,525	50	8.5 - 11.0	9.0	13.1	10.8	36.9	22.5
37X13.50R17/8	5779		85	3,195	50	8.5 - 11.0	11.0	13.9	10.8	36.9	22.5
LT325/60R18/10	5780	33X13.50R18LT	74	3,525	65	9.0 - 12.0	9.5	13.3	10.5	33.4	23.0
LT375/50R18/10	5781	33X15.50R18LT	81	3,525	65	10.0 - 13.0	12.0	15.4	12.2	33.0	23.0
LT325/65R18/10	5782	35X13.50R18LT	78	3,860	65	9.0 - 12.0	9.5	13.5	10.6	34.9	23.0
LT375/60R18/8	5783	36X15.50R18LT	89	3,640	50	10.0 - 13.0	11.0	15.0	12.0	35.9	23.0
LT395/65R18/6	5785	38X15.50R18LT	96	3,415	35	11.0 - 14.0	12.0	15.7	12.2	37.9	23.0
40X13.50R18/8	5786		98	3,525	50	8.5 - 11.0	11.0	13.6	10.8	39.8	23.0
LT325/50R20/10	5720	33X13.50R20LT	72	3,085	65	10.0 - 12.0	10.0	13.3	10.3	33.1	21.0
35X13.50R20/10	5722		76	3,305	65	9.0 - 12.0	11.0	13.6	10.6	35.0	21.0
36X15.50R20/10	5723		88	3,525	65	11.0 - 13.0	12.0	15.3	12.2	35.8	21.0
38X15.50R20/8	5724		99	3,525	50	11.0 - 13.0	12.0	15.7	12.2	37.9	21.0
40X13.50R20/8	5725		96	3,970	50	8.5 - 11.0	11.0	13.6	10.8	39.8	20.5

SPECIALTY LIGHT TRUCK SIZES FEATURE 3 PLY SIDEWALL AND 6 PLY TREAD FOR ADDED STRENGTH AND PUNCTURE RESISTANCE

MICKEY THOMPSON



BAJA CLAW *POLYESTER/FIBERGLASS BELTED, BLACK LETTERS*

TIRE SIZE	CODE #	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
33X13.50-15/6	2654	58	2,300	30	8.0 - 10.0	10.0	13.0	9.7	33.0	21.0
35X13.50-15/6	2658	60	2,640	30	10.0 - 12.0	10.0	13.5	10.0	35.0	21.0
35X15.50-15/6	2659	73	2,795	30	10.0 - 12.0	12.0	15.0	11.5	35.0	21.0
16/38.5-15/4	2672	103	2,450	30	10.0 - 12.0	12.0	17.5	12.5	39.0	21.0
19.5/46-15/6	2674	138	3,200	30	12.0 - 16.0	14.0	20.5	14.6	46.0	28.0
33X13.50-16/6	2664	58	2,210	30	8.0 - 10.0	10.0	13.0	9.7	33.0	21.0
35X13.50-16/6	2668	60	2,560	30	10.0 - 12.0	10.0	13.5	10.0	35.0	21.0
16/38.5-16/6	2676	102	2,400	30	10.0 - 12.0	12.0	16.5	12.5	39.0	21.0
19.5/46-16/6	2678	137	3,500	30	12.0 - 16.0	14.0	20.5	14.6	46.0	28.0
16/38.5-16.5/6	2686	101	2,400	30	9.75 - 12.0	12.0	16.5	12.5	39.0	21.0
19.5/46-16.5/6	2688	138	3,500	30	12.0 - 16.0	14.0	20.3	14.6	46.0	28.0
19.5/46-20/6	2698	149	3,500	30	12.0 - 16.0	14.0	18.8	14.6	46.0	28.0



BAJA BELTED *POLYESTER/FIBERGLASS BELTED, OUTLINE WHITE LETTERS*

TIRE SIZE	CODE #	WEIGHT	MAX LOAD SINGLE	MAX PSI	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER	TREAD DEPTH
36X12.50-15/4	2032	58	2,145	20 psi	9.0 - 10.0	10.00	13.0	9.0	36.0	19.0
36X14.50-15/4	2034	69	2,295	20 psi	10.0 - 12.0	10.00	14.9	11.3	36.0	19.0
15/39-15/4	2072	77	2,195	25 psi	10.0 - 12.0	10.00	15.2	11.5	39.0	21.0
18/39-15/4	2078	89	2,315	25 psi	12.0 - 14.0	12.00	18.0	14.5	39.0	21.0
34X11.50-16/4	2073	52	2,440	30 psi	8.0 - 10.0	8.00	11.9	8.5	34.0	16.0
36X14.50-16.5/6	2035	73	3,045	30 psi	9.75 - 12.0	9.75	14.9	11.3	36.0	19.0
15/39-16.5/6	2086	77	2,410	30 psi	9.75	9.75	15.2	11.5	39.0	21.0
18/39-16.5/6	2080	92	2,540	30 psi	12.0 - 14.0	12.00	18.0	14.5	39.0	21.0

OFF-ROAD RACE TIRES

TIRE SIZE	CODE #	PRODUCT MODEL	WEIGHT	APPROVED RIMS	MEASURING RIM WIDTH	SECTION WIDTH	TREAD WIDTH	OVERALL DIAMETER
30/7.0-15	2548	Baja Pro	28	3.0 - 6.0	4.0	6.9	4.9	30
33/9.0-15	2554	Baja Pro	37	4.0 - 8.0	7.0	9.6	7.8	33
35/10.0-15	2555	Baja Pro	40	4.0 - 8.0	7.0	10.3	7.8	35
30x7.50-15	2550	Stonewall	30	5.0 - 7.0	6.0	8.3	6.7	30
33x10.50-15	2553	Desert King	40	7.0 - 9.0	8.0	11.3	8.7	32
E78-15	2551	Mini Mag	21	4.0 - 6.0	4.0	6.5	5.2	27
37x13.00-17LT	2640	Competition Claw	73	8.0 - 12.0	8.0	12.5	9.7	37
34X11.50-16LT	2073	Baja Belted	52	8.0 - 10.0	8.0	11.9	8.5	34
31x7.50-15	4030	Baja Belted HP	28	5.0 - 7.0	6.0	9.4	6.4	31



Baja Pro



Stonewall



Desert King



Mini Mag



Competition Claw



Baja Belted HP

PARNELLI JONES

DIRT GRIPZ

CODE #	ITEM CODE	TIRE SIZE	SIDE WALL	LR	PR	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	DUAL MAX LOAD	DUAL MAX PSI	SINGLE MAX LOAD	SINGLE MAX PSI	SECTION WIDTH	OVERALL DIAMETER
PJ-05R	19548	31X10.50R15	BLK	C	6	54	7	21			2270	50	10.7	31.5
PJ-01R	18482	33X12.50R15	BLK	C	6	66	8.5	21			2225	35	12.5	33.3
PJ-04R	19549	35X12.50R15	BLK	C	6	70	8.5	21			2535	35	31.1	35.1
PJ-02R	18483	36X14.50R15	BLK	C	6	84.9	10	21			2910	35	14.5	36.1
PJ-20R	19550	37X12.50R15	BLK	C	6	78.5	8.5	21			2895	35	13.5	36.7
PJ-03R	19081	38X15.50R15	BLK	C	6	95.5	11	21			3000	35	15.3	38.2
PJ-06R	19551	31X10.50R16	BLK	E	10	58.5	7	21			2910	80	10.3	31.5
PJ-12R	19552	33X12.50R16	BLK	E	10	72	8.5	21			3195	65	12.4	33.3
PJ-07R	19553	35X12.50R16	BLK	E	10	82.5	8.5	21			3640	65	12.8	35.3
PJ-13R	19554	36X14.50R16	BLK	E	10	95	10	21			3640	65	14.5	36.1
PJ-21R	19555	37X12.50R16	BLK	E	10	90	8.5	21			3640	65	13.3	36.7
PJ-19R	19556	38X15.50R16	BLK	E	10	102	11	21			3640	65	15.3	38.2
PJ-27R	31469	LT285/75R16	BLK	D	8	67	8.5	21			3640	65	10.4	36.7
PJ-14R	19557	35X12.50R16.5	BLK	E	10	81.5	8.5	21			3840	65	12.6	35.3
PJ-11R	19558	36X14.50R16.5	BLK	E	10	95	10	21			3640	65	14.5	36.1
PJ-22R	19559	37X12.50R16.5	BLK	E	10	90.5	8.5	21			3970	65	13.3	36.7
PJ-18R	19560	38X15.50R16.5	BLK	E	10	101	11	21			3640	65	15.3	38.2
PJ-23R	19561	37X12.50R17	BLK	E	10	91.5	7.5	21	3000	65	3305	65	11.7	33.6
PJ-28R	35440	LT265/70R17	BLK	E	10	54	7	21	2270	50	2470	50	10.7	32.6
PJ-25R	28178	33X12.50R17	BLK	E	10	73.5	8.5	21			3085	65	12	33.3
PJ-26R	28179	35X12.50R17	BLK	E	10	84.5	8.5	21			3640	65	12.3	35.3
PJ-24R	25494	38X15.50R17	BLK	E	10	101	11	21			3640	65	15.1	38.2
PJ-30R	40076	35X12.50R18	BLK	D	8	76								
PJ-32R	40077	36X14.50R18	BLK	D	8	92								
PJ-33R	40078	36X14.50R20	BLK	D	8	93								
PJ-34R	39851	37X12.50R18	BLK	D	8	82.16								
PJ-35R	39852	37X12.50R20	BLK	D	8	82								
PJ-37R	40513	38X15.50R20	BLK	D	8	96								



SOLIDEAL



SOLIDEAL HAULER XD44

INDUSTRIAL

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
10-16.5	10		30411148X	8.25	75	4718	5	31	44	86.0
12-16.5	10			9.75	64	5611	5	33	44	89.0



SOLIDEAL LIFEMASTER SKZ

INDUSTRIAL

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
10-16.5	8	20687	30Z11146	8.25	60	4134	5	31	37	72.0
10-16.5	10	20696	30Z11148	8.25	75	4718	5	31	37	73.0
12-16.5	10	20697	30Z11154	9.75	64	5611	5	33	37	89.0
12-16.5	12	20698	30Z11155	9.75	80	6349	5	33	38	97.0
33X15.5-16.5	14		30Z11157	12.00	70	6944	5	0	38	0.0
14-17.5	10		30Z11158	10.5	55	6845	5	0	48	0.0
14-17.5	14		30Z11160	10.5	80	8543	5	37	48	144.0



SOLIDEAL HAULER LOADER SKS

INDUSTRIAL

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
5.70-12	6	17953	30411132	4.50I	60	0	5	23	11	0.0
23X8.5-12	6	4881	30411134	7.00I	50	1819	5	23	16	25.0
23X8.5-12	10		30411135	7.00I	84	0	5	23	16	0.0
23X8.5-12	12			7.00I	100	2723	5	23	16	31.0
27X8.5-15	6	4882	30411138	7JA	44	2480	5	27	12	32.0
27X9.5-15	6		30411139	8.50	44	2557	5	27	20	46.0
27X10.5-15	8		30411140	8.50	59	3064	5	28	20	46.0
31X15.5-15	8	17954	30411142	13.00	44	3726	5	31	28	82.0
31X15.5-15	10		30411143	13.00	59	0	5	31	28	0.0
31X15.5-15	12		30411141	13.00	75	4916	5	31	28	86.0
10-16.5(30)	8			8.25	60	4134	5	30	17	52.0
10-16.5(30)	10			8.25	75	0	5	30	17	0.0
10-16.5	8	4883	30411146-788	8.25	55	3924	5	31	17	54.0
10-16.5	10	45623	30411148-788	8.25	75	4718	5	31	17	54.0
10-16.5	12		30411149-788	8.25	90	5302	5	31	17	58.0
31.5X13-16.5	10		30411150	9.75	70	5368	5	31	17	0.0
12-16.5	8		30411152	9.75	50	0	5	32	20	0.0
12-16.5	10			9.75	60	5357	5	32	20	78.0
12-16.5	10	4884	30411154	9.75	64	5611	5	32	20	0.0
12-16.5	12		30411155	9.75	80	6349	5	33	17	81.0
33X15.5-16.5	12			12.00	59	6393	5	33	22	108.0
33X15.5-16.5	14	34708	30411157	12.00	70	6944	5	33	22	108.0
14-17.5	10	39665	30411158	10.5	55	6845	5	36	30	0.0
14-17.5	10			10.5	55	6845	5	0	48	0.0
14-17.5	14	4885	30411160	10.5	80	8543	5	37	30	115.0
380/65-19.5(14.5-19.5)	12			11.75	60	9193	5	39	31	0.0
380/65-19.5(14.5-19.5)	14	17955	30411164	11.75	80	11177	5	38	31	139.0
380/65-19.5(14.5-19.5)	16			11.75	100	13228	5	38	31	143.0
15-19.5	8			11.75	40	7176	5	0	31	0.0
15-19.5	10		30411165	11.75	50	8256	5	0	31	0.0
15-19.5	12		30411166	11.75	60	9193	5	40	31	146.0

SOLIDEAL

SOLIDEAL HAULER SKS *continued*

INDUSTRIAL

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
15-19.5	14	4886	30411168	11.75	80	11177	5	40	31	146.0
15-19.5	16		30411169	11.75	0	0	5	0	31	0.0
385/65-22.5(15-22.5)	12			11.75	72	12676	5	43	31	170.0
385/65-22.5(15-22.5)	16		30411172	11.75	100	15520	5	437	31	181.0
385/65-22.5(15-22.5)	20	17956	30411170	11.75	129	18353	5	44	31	219.0

SOLIDEAL SKS XTRA WALL

INDUSTRIAL

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
23X8.5-12	4			7.00I	32	1411	5	0	18	0.0
23X8.5-12	6		10X11134	7.00I	50	1819	5	23	18	22.0
23X8.5-12	12		10X11135	7.00I	100	2723	5	0	18	0.0
26X12-12	8		10X11137	10.50	50	3020	5	26	30	45.0
26X12-12	10	7454	10X11136	10.50	64	3593	5	26	30	45.0
27X8.5-15	6		10X11138	7JA	44	2480	5	27	17	26.0
27X8.5-15	8		10X11190	7JA	59	2888	5	27	17	28.0
10-16.5	6	20187	10X11144	8.25	45	3505	5	30	20	48.0
10-16.5	8	20188	10X11146	8.25	60	4134	5	30	20	48.0
10-16.5	10		10411148	8.25	75	4718	5	31	20	51.0
10-16.5	12		10X11149	8.25	90	5302	5	30	20	56.0
12-16.5	8	20186	10X11152	9.75	50	4806	5	33	20	63.0
12-16.5	10	20185	10X11154	9.75	64	5611	5	32	20	67.0
12-16.5	12		10X11155	9.75	80	6349	5	32	16	71.0
14-17.5	10		10X11158	10.50	55	6845	5	36	35	94.0
14-17.5	12		10411159	10.50	69	7826	5	36	35	108.0



SOLIDEAL SKIDSTEER SKS

INDUSTRIAL

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
5.70-12	6	17950	10411132	4.50I	60	1455	5	22	10	16.0
23X8.5-12	4		10411194	7.00I	32	1411	5	0	18	0.0
23X8.5-12	6	4855	10411134	7.00I	50	1819	5	22	18	22.0
23X8.5-12	10		10411133	7.00I	84	0	5	23	18	0.0
23X8.5-12	12		10411135	7.00I	100	2723	5	23	18	0.0
27X10-12	14	20685	10411108	8.00G	100	7815	16	28	24	53.0
7.00-15	6		10411031	5.50	59	3175	5	31	18	44.0
27X8.5-15	6	4856	10411138	7JA	44	2480	5	27	17	30.0
27X8.5-15	8		10411140	7JA	59	2888	5	27	17	28.0
31X15.5-15	8		10411142	13.00	44	3726	5	30	29	73.0
26x12-16.5	10			9.75	57	3593	5	26	30	46.0
10-16.5	6	25492	10411144	8.25	45	3505	5	30	20	49.0
10-16.5	8	4857	10411146	8.25	55	3924	5	30	20	45.0
10-16.5	8		10411147	8.25	60	4134	5	30	20	48.0
10-16.5	10		10411148	8.25	75	4718	5	30	20	51.0
12-16.5	8	7451	10411152	9.75	50	4806	5	33	20	62.0
12-16.5	10	4858	10411154	9.75	64	5611	5	33	20	67.0
14-17.5	10	20686	10411158	10.50	55	6845	5	36	35	94.0
14-17.5	12	25489	10411159	10.50	69	7826	5	36	35	108.0
14-17.5	14			10.50	80	0	0	0	0	0.0



SOLIDEAL

SOLIDEAL MPT / TRACTIONMATER R1 / DUMPER PNEUMATICS



SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
I3										
10.5-18	8			9 x 18	43	3704	31	0	31	0.0
10.5-18	10		10911310	9 x 18	54	4200	31	35	31	77.0
12.5-18	10		10911315	11x18	43	4442	31	0	28	0.0
12.5-18	12		10911320	11x18	50	4817	31	39	28	105.0
10.5 - 20	10	53413	10911325	9 x 20	54	4442	31	37	28	72.0
12.5 - 20	10		10911338	11 x 20	43	4564	31	42	30	0.0
12.5 - 20	12	41114	10911340	11 x 20	50	4938	31	41	30	0.0
14.5 - 20	10		10911345	11 x 20	36	4938	31	0	34	0.0
14.5 - 20	12		10911350	11 x 20	43	5379	31	0	34	0.0
14.5 - 20	14		10911355	11 x 20	50	5831	31	44	34	143.0
405/70-20	12		10911362	13 x 20	43	7606	25	43	34	128.0
405/70-20	14		10911365	13 x 20	50	8267	25	43	34	132.0
405/70-24	14		10911370	13 x 24	50	8818	25	47	37	154.0
R1										
26X12-12	10			10.50	64	3593	5	0	26	0.0
29x12.5-15	8			10LB	44	0	0	0	0	0.0
31x15.5-15	6			13LB	30	0	0	0	0	0.0
31x15.5-15	8			13.00	44	3726	5	32	26	61.0
10.0/75-15.3	8	20703	10911380	9 x 15.3	44	0	0	0	28	0.0
11.5/80-15.3	8	20705	10911390	9 x 15.3	39	3748	25	34	29	56.0
26x12-16.5	10			9.75	57	3593	5	26	25	38.0
33X15.5-16.5	10			12.00	49	6008	5	0	29	0.0
12.5-18	10			11x18	43	4442	31	0	31	0.0
12.5-18	12			11x18	50	4817	31	39	31	93.0
405/70-20	10		10911358	13 x 20	43	6779	25	0	38	0.0
405/70-20	12		10911360	13 x 20	43	7606	25	0	38	0.0
405/70-20	14		10911367	13 x 20	50	8267	25	44	38	139.0
18-22.5	16			14 x22.5	64	10692	25	47	45	161.0
405/70-24	14		10911368	13 x 24	50	8818	25	47	34	144.0
15.5/80-24	12		10911372	13 x 24	43	9094	25	51	45	151.0
15.5/80-24	14		10911375	13 x 24	50	9921	25	51	45	157.0
15.5/80-24	16			13 x 24	57	10747	25	0	45	0.0
16.5/85-24	8			13 x 24	27	8267	25	52	33	152.0
R4										
10.0/75-15.3	8		10911380	9 x 15.3	44	0	0	0	28	0.0
10.0/75-15.3	10			9 x 15.3	56	0	0	0	28	0.0
11.5/80-15.3	8			9 x 15.3	39	0	0	0	31	0.0
11.5/80-15.3	10			9 x 15.3	49	0	0	0	31	0.0
11.5/80-15.3	14			9 x 15.3	68	0	0	0	31	0.0
12.5-18	10		10911390	11x18	43	4442	31	39	30	90.0
12.5-18	12			11x18	50	4817	31	39	30	104.0
18-22.5	16			14 x22.5	64	10692	25	47	44	196.0

SOLIDEAL

SOLIDEAL HAULER PNEUMATIC FORKLIFT

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD STEER	MAX LOAD DRIVE	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
LT											
5.00-8	10	4860	30211008	3.00D	143	2403	3120	6	19	11	19.0
16X6-8	16	4861	30211076	4.33R	129	2679	3483	6	17	8	17.0
18X7-8	16		30211084	4.33R	143	3638	4729	6	19	13	24.0
18X7-8	18	4863	30211086	4.33R	150	4079	5302	6	19	13	26.0
6.00-9	10	4864	30211010	4.00E	122	2910	3781	6	21	14	28.0
21X8-9	16	17951	30211090	6.00E	129	4299	6074	6	21	11	31.0
6.50-10	10	4865	30211014	5.00F	111	3307	4299	6	23	14	26.0
6.50-10	12			5.00F	129	3638	4729	6	23	14	33.0
23X9-10	18		30211096	6.50F	114	5071	6592	6	23	10	0.0
23X9-10	20	4866	30211098	6.50F	143	5842	7595	6	23	10	53.0
7.00-12	14	4867	30211024	5.00S	129	4674	6074	6	27	14	40.0
23X10-12	16		30211106	8.00G	139	5997	7793	6	24	13	54.0
27X10-12	16	17952	30211110	8.00G	114	6614	8598	6	27	14	64.0
27X10-12	24		30211114	8.00G	143	9370	12180	6	27	14	71.0
7.00-15	14	4870	30211032	5.50	129	5677	7385	6	29	16	45.0
7.50-15	14	4871	30211038	6.00	132	6173	8025	6	0	16	45.0
8.25-15	14	4873	30211046	6.50	114	7165	9314	6	33	9	78.0
8.25-15	16		30211048	6.50	132	7826	10174	6	33	9	86.0
8.25-15	18		30211050	6.50	143	8047	10803	6	33	9	85.0
28X9-15(8.15-15)	14	4872	30211118	7.00	129	6393	8311	6	28	16	55.0
28X9-15(8.15-15)	16		30211119	7.00	139	6944	9028	6	0	16	61.0
2.50-15	16	4876	30211120	7.50	118	7385	9601	6	29	16	66.0
2.50-15	18			7.50	136	8047	9480	6	29	16	76.0
2.50-15	20	4875	30211124	7.50	150	8818	11464	6	29	16	77.0
3.00-15	20	4877	30211126	8.00	136	10747	13977	6	33	20	106.0
28X12.5-15	24	4874	30211128	9.75	143	10196	13261	6	27	16	96.0
32X12.1-15	24	4878	30211130	9.75	143	13228	17196	6	32	20	130.0
10.00-20	16	4879	30211062	7.50	129	11023	13228	6	43	23	177.0
11.00-20	16	45864	30211064	8.00	143	11960	14352	6	43	23	184.0
12.00-20	20	4880	30211068	8.50	143	15102	18122	6	46	23	203.0
PORTMASTER											
12.00-20	20	37915	30P11068	8.50	143	15102	18122	6	45	72	
12.00-20	28		30P11069	8.50	143	15102	18122	6	45	72	
SMOOTH											
8.25-15	16			6.50	132	7826	10174	6	0		92.0
10.00-20	16			7.50	129	11023	13228	6	43		186.0
12.00-20	20			8.50	143	15102	18122	6	45		213.0
HALFTRAC											
10.00-20	16			7.50	129	11023	13228	6	43	23	183.0
12.00-20	20			8.50	143	15102	18122	6	45	23	229.0



SOLIDEAL



SOLIDEAL EXTRA DEEP PNEUMATIC FORKLIFT

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD STEER	MAX LOAD DRIVE	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
4.00-8	6		10211000	2.50C	114	1323	1720	6	17	8	11.0
4.00-8	8	20680	10211002	3.00D	129	1477	1918	6	16	8	12.0
5.00-8	6		10211005	3.00D	89	1819	2370	6	18	9	0.0
5.00-8	8	4842	10211006	3.00D	118	2094	2723	6	18	9	13.0
5.00-8	10		10211008	3.00D	143	2403	3120	6	18	9	14.0
18X7-8	14	4851	10211082	4.33R	129	3197	4156	6	18	9	19.0
18X7-8	16		10211084	4.33R	143	3638	4729	6	18	9	18.0
6.00-9	10	4843	10211010	4.00E	122	2910	3781	6	21	10	21.0
21X8-9	14	4852	10211088	6.00E	129	4299	5589	6	21	14	29.0
6.50-10	10	4844	10211014	5.00F	111	3307	4299	6	23	12	26.0
6.50-10	12		10211016	5.00F	129	3638	4729	6	23	12	28.0
7.50-10	12	20681	10211020	5.50F	114	4541	5908	6	0	13	38.0
7.50-10	16		10211021	5.50F	143	5203	6768	6	25	13	38.0
23X9-10	14		10211092	6.50F	100	4674	6074	6	0	10	41.0
23X9-10	16		10211094	6.50F	114	5071	6592	6	23	10	42.0
23X9-10	18		10211096	6.50F	129	5357	6967	6	22	10	43.0
7.00-12	12	4845	10211022	5.00S	122	4541	5908	6	27	11	37.0
7.00-12	14	17943	10211024	5.00S	129	4674	6074	6	27	11	36.0
23X10-12	14	17948	10211104	8.00G	118	5512	7165	6	23	10	42.0
23X10-12	16			8.00G	139	5997	7793	6	0	10	0.0
27X10-12	16			8.00G	114	6614	8598	6	0	14	60.0
27X10-12	20			8.00G	129	7826	10174	6	27	14	65.0
23X5	6	17947	10211072	3.75P-13	75	2535	3296	6	0	12	25.0
23X5	8			3.75P-13	93	2910	3781	6	0	12	27.0
23X5	10			3.75P-13	111	3285	4266	6	0	12	27.0
7.00-15	12	17944	10211030	5.50	118	5203	6768	6	30	11	49.0
7.00-15	14	4846	10211032	5.50	129	5677	7385	6	30	11	49.0
7.50-15	12	17945	10211036	6.00	114	5842	7595	6	31	26	50.0
7.50-15	14	4847	10211038	6.00	132	6173	8025	6	31	25	0.0
8.25-15	12	17946	10211044	6.50	100	6614	8598	6	34	23	72.0
8.25-15	14	4849	10211046	6.50	114	7165	9314	6	33	25	72.0
8.25-15	16		10211048	6.50	132	7826	10174	6	33	25	72.0
28X9-15(8.15-15)	12		10211116	7.00	118	5842	7308	6	28	25	51.0
28X9-15(8.15-15)	14	4848	10211118	7.00	129	6393	8311	6	28	24	57.0
28X9-15(8.15-15)	16		10211120	7.00	139	6944	9028	6	28	23	57.0
2.50-15	16	4853	10211122	7.50	118	7385	9601	6	29	28	74.0
2.50-15	18		10211120	7.50	129	8047	9480	6	29	28	66.0
2.50-15	20		10211124	7.50	150	8818	11464	6	29	29	66.0
3.00-15	18	4854	10211126	8.00	114	10196	13261	6	32	30	105.0
7.50-16	12	20682	10211056	6.00	114	6393	8311	6	32	27	57.0
9.00-20	14	38949	10211058	7.00	129	9810	11773	6	41	25	103.0
10.00-20	16	4850	10211062	7.50	129	11023	13228	6	42	25	117.0

SOLIDEAL

SOLIDEAL BACKHOE PNEUMATICS

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
F3										
11L-15SL	8		10311154	8LBx15	36	2535	31	31	16	45.0
11L-15SL	10	17957	10311156	8LBx15	51	2337	31	30	16	47.0
11L-16SL	10	4887	10311158	8LBx16	51	2469	31	32	16	50.0
11L-16SL	12		10311160	8LBx16	51	3428	31	32	16	52.0
14.5/75-16.1SL	10	17958	10311162	W11Cx16.1	40	4795	9	37	21	94.0
R4										
10.5/80-18	10	7455	10411200	W9x18	53	2998	19	34	26	61.0
10.5/80-18	12		10411201	W9x18	63	0	0	37	26	0.0
12.5/80-18	10		10411203	W9x18	44	3748	19	38	38	90.0
12.5/80-18	12	7456	10411205	W9x18	53	5842	19	38	38	89.0
12.5/80-18	14			W9x18	61	4674	19	37	38	95.0
14.9-24	8	20702	10411210	W13x24	30	0	0	50	38	0.0
14.9-24	12	21548	10411213	W13x24	41	6393	25	49	38	151.0
16.9-24	8	18940	10411215	W15Lx24	27	5842	25	51	33	182.0
16.9-24	10	18941	10411220	W15Lx24	31	6614	25	51	33	189.0
16.9-24	12	21549	10411225	W15Lx24	37	7165	25	51	33	189.0
17.5L-24	6	21550	10411230	W15Lx24	20	0	0	50	38	0.0
17.5L-24	8	18942	10411235	W15Lx24	27	0	0	50	38	0.0
17.5L-24	10	16769	10411240	W15Lx24	31	6173	25	50	38	183.0
19.5L-24	8			W16Lx24	24	6008	25	53	35	195.0
19.5L-24	10	17960	10411245	W16Lx24	27	6779	25	52	35	212.0
19.5L-24	12	18943	10411250	DW16Ax24	33	7606	25	52	35	230.0
21L-24	10	31130	10411255	W18Lx24	26	7385	25	55	48	250.0
21L-24	12	31137	10411260	DW18Ax24	31	8543	25	55	48	260.0
21L-24	16			DW18Ax24	40	0	0	0	0	0.0
18.4-26	12	33262	10411265	W16Lx26	36	8818	25	56	35	238.0
16.9-28	8	33261	10411270	W15Lx28	27	0	0	57	42	0.0
16.9-28	10		10411275	W15Lx28	31	6944	25	56	42	214.0
16.9-28	12	21551	10411280	W15Lx28	37	7826	25	56	42	220.0
18.4-28	10			W16Lx28	30	0	0	59	49	0.0
18.4-28	12	21552	10411290	W16Lx28	36	0	0	59	49	0.0
R1										
12.5/80-18	12		10411205	W9x18	53	5842	19	39	38	93.0
18.4-26	12			W16Lx26	36	8818	25	56	45	214.0
16.9-28	12			W15Lx28	37	7826	25	56	43	217.0



SOLIDEAL GRADER G2/L2 PNEUMATICS

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
13.00-24 TG	10			8.00TGx24	0	0	0	51	33	0.0
13.00-24 TG	12	9554	10411180	8.00TGx24	43	6008	25	50	33	161.0
13.00-24 TG	14		10411182	8.00TGx24	0	0	0	51	33	0.0
13.00-24 TG	16		10411183	8.00TGx24	0	0	0	51	33	0.0
14.00-24 TG	12	9555	10411184	8.00TGx24	36	6779	25	52	33	183.0
14.00-24 TG	16		10411186	8.00TGx24	79	0	0	52	33	183.0



SOLIDEAL

SOLIDEAL WHEEL LOADER PNEUMATICS



SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
L2										
15.5-25	12	54122	104114002	12.00/1.3	57	12346	6	50	31	160.0
15.5-25	12			12.00/1.3	32	5842	25	0	31	0.0
15.5-25	12			12.00/1.3	36	7165	31	0	31	0.0
15.5-25	16	54119	104114052	12.00/1.3	79	15212	6	50	31	168.0
15.5-25	16			12.00/1.3	39	6614	25	0	31	0.0
15.5-25	16			12.00/1.3	43	8818	31	0	31	0.0
17.5-25	12	54123	104114102	14.00/1.5	50	13558	6	53	33	192.0
17.5-25	12			14.00/1.5	29	6393	25	0	33	0.0
17.5-25	12			14.00/1.5	32	8047	31	0	33	0.0
17.5-25	16	37329	104114152	14.00/1.5	68	16094	6	0	33	0.0
17.5-25	16			14.00/1.5	39	7385	25	0	33	0.0
17.5-25	16			14.00/1.5	43	9370	31	0	33	0.0
20.5-25	12	54124	104114202	17.00/2.0	36	14771	6	0	38	0.0
20.5-25	12			17.00/2.0	25	7826	25	0	38	0.0
20.5-25	12			17.00/2.0	29	9921	31	0	38	0.0
20.5-25	16	37333	104114252	17.00/2.0	50	18188	6	59	38	293.0
20.5-25	16			17.00/2.0	32	8818	25	0	38	0.0
20.5-25	16			17.00/2.0	39	12015	31	0	38	0.0
L3										
15.5-25	12	54125	10411400R	12.00/1.3	57	12346	6	0	33	203.0
15.5-25	12			12.00/1.3	32	5842	25	0	33	0.0
15.5-25	12			12.00/1.3	36	7165	31	0	33	0.0
15.5-25	16	54126	10411405R	12.00/1.3	79	15212	6	0	33	0.0
15.5-25	16			12.00/1.3	39	6614	25	0	33	0.0
15.5-25	16			12.00/1.3	43	8818	31	0	33	0.0
17.5-25	12	37330	10411410R	14.00/1.5	50	13558	6	0	35	0.0
17.5-25	12			14.00/1.5	29	6393	25	0	35	0.0
17.5-25	12			14.00/1.5	32	8047	31	0	35	0.0
17.5-25	16	37331	10411415R	14.00/1.5	68	16094	6	0	35	0.0
17.5-25	16			14.00/1.5	39	7385	25	0	35	0.0
17.5-25	16			14.00/1.5	43	9370	31	0	35	0.0
17.5-25	20	54127	10411530R	14.00/1.5	82	18188	6	0	35	280.0
17.5-25	20			14.00/1.5	57	11023	31	0	35	0.0
20.5-25	16	37334	10411425R	17.00/2.0	50	18188	6	59	40	348.0
20.5-25	16			17.00/2.0	32	8818	25	0	40	0.0
20.5-25	16			17.00/2.0	39	12015	31	0	40	0.0
20.5-25	20	54128	10411430R	17.00/2.0	64	20944	6	60	40	351.0
20.5-25	20			17.00/2.0	46	13228	31	0	40	0.0
23.5-25	16	54129	10411435R	19.5/2.5	43	20944	6	64	47	529.0
23.5-25	16			19.5/2.5	29	10472	25	0	47	0.0
23.5-25	16			19.5/2.5	32	13558	31	0	47	0.0
23.5-25	20	54130	10411438R	19.5/2.5	54	24030	6	62	47	483.0
23.5-25	20			19.5/2.5	43	16094	31	0	47	0.0
26.5-25	20	54132	10411520R	22.00/3.0	50	29101	6	69	50	617.0
26.5-25	20			22.00/3.0	36	18188	31	0	50	0.0
26.5-25	28			22.00/3.0	68	34171	6	70	50	0.0
26.5-25	28			22.00/3.0	50	22046	31	0	50	0.0

SOLIDEAL

SOLIDEAL EXCAVATOR PNEUMATICS

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
8.25-20	14		10411057	6.50-20	129	0	0	39	25	95.0
9.00-20	14	20699	10411058	7.00-20	122	0	0	41	25	92.0
10.00-20	16	20700	10411062	7.50-20	122	9348	6	42	33	103.0
11.00-20	16	30256	10411064	8.00-20	122	0	0	43	33	132.0



SOLIDEAL GSE AIRPORT PNEUMATICS

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
ZZRIB										
6.90-9	10		10811204	4.00E	122	2976	16	22	21	27.0
6.50-10	10	20684	10811014	5.00E	111	3307	16	23	0	28.0
8.00-16.5	8			6.00	80	3638	5	29	0	0.0
RIB										
4.00-8	8	20683	10311000	3.25I	129	1477	16	17	9	12.0

SOLIDEAL COMPACTOR PNEUMATICS

SIZE	PLY	CODE #	ITEM #	RIM WIDTH	MAX PSI	MAX LOAD	SPEED	OVERALL DIAMETER	TREAD DEPTH	WEIGHT
7.50-15 NHS	6			6.00-15	50	0	0	30	-	0.0
7.50-15 NHS	10			6.00-15	86	0	0	33	-	0.0
7.50-15 NHS	12	7452		6.00-15	118	5765	6	31	-	56.0
7.50-15 NHS	14	4859		6.00-15	122	6250	6	31	-	56.0
8.50/90-15K	6	20701		6.00G-15	50	0	0	30	-	41.0
7.50-16 NHS	6			6.00-16	0	0	0	35	-	0.0
9.00-20	10			7.00-20	0	0	0	0	-	0.0
9.00-20	12			7.00-20	0	0	0	0	-	0.0
9.00-20	14			7.00-20	107	0	0	41	-	0.0
11.00-20	12		10111063	8.00-20	0	0	0	0	-	0.0
11.00-20	16		10111064	8.00-20	105	12004	6	42	-	152.0
11.00-20	18		10111065	8.00-20	0	0	0	0	-	0.0



